

# County Surveyor's Record, Douglas County, Oregon

13129

## Subdivision of Section 19, T. 24 S., R. 6 W.

CHAINS	
23.05	Dirt road, 20 lks. wide, bears S. 60° E. and N. 60° W.
28.00	Spur ridge, bears N. 30° W. and S. 30° E.; desc. 165 ft. over SW. slope.
30.30	Dirt road, 20 lks. wide, bears S. 15° E. and N. 15° W.
38.55	Creek, 3 lks. wide, course N. 20° W.; asc. 10 ft. over NE. slope.
39.60	Spur, slopes N.; desc. 15 ft. over W. slope.
42.11	The S. 1/16 sec. cor. of sec. 19 only, on the W. bdy. of the Twp.
<p>From the center W 1/16 sec. cor. of sec. 19.</p> <p>N. 0° 22' E., along the N. and S. center line of the NW<math>\frac{1}{4}</math>.</p> <p>Descend 130 ft. over N. slope.</p>	
3.70	Gully, drains N. 40° E.; desc. 50 ft. along E. slope.
7.00	Spur, slopes N. 40° E.; desc. 30 ft. over NE. slope.
8.90	Slope breaks sharply, desc. 25 ft. over N. slope to creek bottom.
9.80	Little Canyon Creek, 20 lks. wide, course N. 45° W.; asc. 125 ft. over SW. slope, changing to W. slope.
11.00	Road, hard-surfaced, 50 lks. wide, bears S. 40° E. curving N. 30° W.
20.17	Point for the NW 1/16 sec. cor. of sec. 19, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$ .
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.
	NW 1/16 S 19 1962
	from which
	A fir, 28 ins. diam., bears S. 51° W., 45 lks. dist., mkd. NW 1/16 S19 BT.
	A fir, 8 ins. diam., bears N. 10° W., 36 lks. dist., mkd. NW 1/16 S19 BT.
	Descend 25 ft. over NW. slope.
21.50	Head of gully, drains S. 65° W.; asc. 65 ft. over SW. slope.
22.75	Road, dirt, 15 lks. wide, bears S. 20° E. and N. 20° W.
28.60	Spur, slopes W.; asc. 10 ft. along W. slope.
30.00	Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.; transmission line, bears N. 25° W. and S. 25° E.
35.50	Creek, 3 lks. wide, course S. 40° W.; asc. 60 ft. over SE. slope.
37.60	Spur, slopes S. 30° W.; desc. 15 ft. over NW. slope.
40.35	True point for the W 1/16 sec. cor. of secs. 18 and 19.