

County Surveyor's Record, Douglas County, Oregon

T. 20 S., R. 9 W.

Group 350

CHAINS

The following field notes describe the remonumentation of an original corner point, T. 20 S., R. 9 W., as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collecteral or Physical Evidence of Corner Points, With New Accessories When Needed".

The remonumentation of the corner was requested by the Coos Bay District Manager for administrative purposes of the Bureau of Land Management.

(Remonumentation of a corner established in 1891 by William Thiel and remonumented in 1953 by Joseph S. Gawron.)

The cor. of secs. 1 and 2 only, on the N. bdy. of T. 20 S., R. 9 W. The iron post set in 1953 has slid out of position and the true position is determined at record bearing and distance from the original, the 1953 bearing trees.

Reset the iron post, 3 ft. long, 2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base to top, with brass cap marked

T 19 S R 9 W
S 36

S 2 | S 1

T 20 S R 9 W
1953

from which the original bearing trees

A down Fir, 36 ins. diam., bears N. 45° E., 14 lks. dist.

A chinquapin stub, 12 ins. diam., bears S. 37½° E., 10 lks. dist., with a healed blaze.

And the 1953 bearing trees

A down fir, 35 ins. diam., bears S. 25° E., 70 lks. dist., marked T20S R9W S1 BT.

An alder, 13 ins. diam., bears S. 60° W., 28 lks. dist., marked T20S R9W S2 BT.

and a new bearing tree

A fir, 30 ins. diam., bears S. 59° E., 30 lks. dist., marked T20S R9W S 1 BT.