

County Surveyor's Record, Douglas County, Oregon

T. 21 S., R. 9 W.

CHAINS

All of the corners remonumented in Township 21 South, Range 9 West, under this assignment, were established by Alonzo Gesner in 1893.

The following field notes describe the remonumentation of certain original corner points, T. 21 S., R. 9 W., as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, With New Accessories When Needed".

The remonumentation of corners was requested by the Coos Bay District Manager for administrative purposes of the Bureau of Land Management.

The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, determined at record bearing and distance from an original bearing tree:

A fir, 38 ins. diam., bears N. 70° E., 20 lks. dist., with the scribe mark S visible on opened blaze.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 21 S R 9 W

$\frac{1}{4}$
 S 10 | S 11
 1963

from which a new bearing tree

A hemlock, 10 ins. diam., bears S. 66° W., 69 lks. dist., marked $\frac{1}{4}$ S10 BT.

The cor. of secs. 2, 3, 10 and 11, determined at record bearing and distance from the remaining original bearing trees:

A fir, 43 ins. diam., bears S. 41° E., 40 lks. dist., with partially opned blaze.

A down fir, 30 ins. diam., bears S. $40\frac{1}{2}^{\circ}$ W., 63 lks. dist., with partially opened blaze.

A fir stub, 40 ins. diam., bears N. 44° W., 42 lks. dist., with scribe marks T21S R visible on split open face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

T 21 S R 9 W
 S 3 | S 2
 S 10 | S 11
 1963

from which a new bearing tree

A fir, 42 ins. diam., bears S. $72\frac{1}{2}^{\circ}$ E., 19 lks. dist., marked., T21S R9W S11 BT.