

Remonumentation, Original Corner Points, T. 21 S., R. 9 W.

## CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 2 and 3, determined at record bearing and distance from the original bearing trees:

A hemlock, 18 ins. diam., bears N.  $87\frac{1}{4}^{\circ}$  E., 30 lks. dist., with the scribe mark S on partially healed blaze.

A fir, 64 ins. diam., bears N.  $20\frac{1}{4}^{\circ}$  W., 91 lks. dist., with the scribe mark S on opned blaze.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

T 21 S R 9 W  
 $\frac{1}{4}$   
 S 3 | S 2  
 1963

from which a new bearing tree

A hemlock, 14 ins. diam., bears N.  $39\frac{1}{2}^{\circ}$  W., 24 lks. dist., marked  $\frac{1}{4}$  S 3 BT.

The  $\frac{1}{4}$  sec. cor. secs. 15 and 16, determined at record distance from the original bearing trees:

A fir, 48 ins. diam., bears N.  $5\frac{1}{2}^{\circ}$  E., 88 lks. dist., with fragmentary scribe marks visible on open blaze. (Record bearing, N.  $8^{\circ}$  E.)

A cedar, 25 ins. diam., bears N.  $31^{\circ}$  W., 83 lks. dist., with scribe marks  $\frac{1}{4}$  S visible on partially healed blaze. (Record bearing, N.  $32^{\circ}$  W.)

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked

T 21 S R 9 W  
 $\frac{1}{4}$   
 S 16 | S 15  
 1963

from which a new bearing tree

A fir, 50 ins. diam., bears N.  $76\frac{1}{2}^{\circ}$  E., 61 lks. dist., marked  $\frac{1}{4}$  S15 BT.

The corner of secs. 9, 10, 15 and 16, which is monumented with a sandstone, 18 x 9 x 8 ins., firmly set, with 4 (four) grooves on the S. face, and 3 (three) grooves on the E. face, from which original bearing trees:

A madrone, 9 ins. diam., bears N.  $25\frac{1}{2}^{\circ}$  E., 73 lks. dist., with no marks remaining. (Record, 75 lks. dist.)

A rotted fir stump, bears S.  $76^{\circ}$  E., 8 lks. dist., with no marks remaining. (Record bearing S.  $82\frac{1}{2}^{\circ}$  E.)

At the corner point