

Remonumentation, Original Corner Points, T. 28 S., R. 9 W.

CHAINS

The cor. of secs. 13, 18, 19 and 24, on the W. bdy of the Tp., determined at record bearing and distance from the original bearing trees:

A cedar, 50 ins. diam., bears N. 55° E., 42 lks. dist., with scribe marks T28S R9W S visible on partially healed blaze.

A maple, 30 ins. diam., bears S. 77° E., 38 lks. dist., with no marks visible on partially healed blaze.
(Record bearing, S. 83° E.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 28 S
R 10 W R 9 W
S 13 | S 18
S 24 | S 19
1962

From which new bearing trees and a bearing object:

A maple, 25 ins. diam., bears N. 46° E., 70 lks. dist., mkd. T28S R9W S18 BT.

A myrtle, 35 ins. diam., bears S. 42° E., 24 lks. dist., mkd. T28S R9W S19 BT.

A fir, 24 ins. diam., bears West, 55 lks. dist., mkd. T28S R10W S24 BT.

A sandstone outcrop, 15 ft. high, bears N. 45° W., 33 lks. dist., mkd. B X O.

Corner Remonumentation on the East Boundary of
T. 28 S., R. 9 W.
(Remonumenting a corner established
by Dennis Hathorn in 1855)

The cor. of secs. 19, 24, 25 and 30, on the E. bdy of the Township, monumented with an iron pipe, 1¼ ins. diam., firmly set, protruding 14 ins. above the ground, with brass cap mkd. Doug. County Surveyor's Office.

Doug. Co. Surveyors Office
T 28 S
R 9 W R 8 W
S
24 | 19
25 | 30
1957
Doug. Co. Coos Co.

from which the three remaining original bearing trees:

A fir, 48 ins. diam., bears N. 78° E., 31 lks. dist., with a healed blaze.

A rotted hemlock stump, bears S. 50° E., 5 lks. dist., with no marks remaining.