

County Surveyor's Record, Douglas County, Oregon

Remonumentation, Original Corner Points, T. 28 S., R. 9 W.

CHAINS

A rotted fir stump, bears S. 65° W., 5 lks. dist.,
with no marks remaining.

and the County Surveyor's bearing trees:

A hemlock, 12 ins. diam., bears N. 44° E., 60 lks.
dist., mkd. T28S R8W S19 BTDCS

A hemlock, 12 ins. diam., bears S. $80\frac{1}{4}^{\circ}$ E., $25\frac{1}{2}$ lks.
dist., mkd. T28S R8W S30 BT DCS.

A down hemlock, 8 ins. diam., bears S. $58\frac{3}{4}^{\circ}$ W.,
15 lks. dist., mkd. T28S R9W S25 BT DCS.

A down hemlock, 36 ins. diam., bears N. $85\frac{1}{2}^{\circ}$ W.,
31 lks. dist., mkd. T28S R9W S24 BT DCS.

and two new bearing trees:

A hemlock, 10 ins. diam., bears S. $12\frac{1}{2}^{\circ}$ W., $30\frac{1}{2}$ lks.
dist., mkd. T28S R9W S25 BT.

A hemlock, 13 ins. diam., bears N. 32° W., 138 lks.
dist., mkd. T28S R9W S24 BT.

Add the mks. BLM 1962 to the County Surveyor's Brass Cap.

Corner Remonumentation on the Subdivisional Lines of
T 28 S., R. 9 W.
(Remonumenting corners established by
W. S. Chapman, in 1875)

The cor. of secs. 23, 24, 25 and 26, monumented with an iron
pipe, $1\frac{1}{2}$ ins. diam., firmly set, protruding 10 ins. above
the ground, with a $\frac{3}{4}$ in. steel rod inside, and mkd. with
a seal, number 401, from which the ~~three~~ remaining original
bearing trees:

A hemlock stub, which has slid down the hill, 20 ins.
diam., bears N. 15° E., 4 lks. dist., no marks
remaining on opened blaze. (Record, N. 16° E.,
50 lks. dist.)

A fir stump, 54 ins. diam., bears S. 46° E., 24 lks.
dist., no marks remaining on opened blaze.

An uprooted and moved sawed fir stump, bears N. 82° W.,
13 lks. dist., with scribe marks 28 S visible on
opened blaze. (Record, N. 47° W., 23 lks. dist.)

and a tree not of record:

A hemlock, 9 ins. diam., bears S. 31° E., 255 lks. dist.,
mkd. S25 BT.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the
ground, with brass cap mkd.

T28 S R 9 W	
S 23	S 24
S 26	S 25
1962	

from which new bearing trees: