

CHAINS

Remonumentation, Original Corner Points, T. 28 S., R. 9 W.

A sawed fir stump, 50 ins. diam., bears N. 17° E.,
95 lks. dist., mkd. T28S R9W S24 BT.

A sawed hemlock stump, 40 ins. diam., bears S. 48° E.,
159 lks. dist., mkd. T28S R9W S25 BT.

A sawed hemlock stump, 40 ins. diam., bears S. 5° W.,
75½ lks. dist., mkd. T28S R9W S26 BT.

A fir, 40 ins. diam., bears N. 31° W., 89 lks. dist.,
mkd. T28S R9W S23 BT.

Reset iron pipe alongside iron post.

The ¼ sec. cor. of secs. 24 and 25, determined at record
bearing and distance from the original bearing trees;

A broken hemlock stump, bears N. 69° W., 20 lks. dist.,
with old axe marks on rotted blaze.

A rotten hemlock stump, bears S. 48° W., 57 lks. dist.,
with no marks remaining.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the
ground, with brass cap mkd.

T 28 S R 9 W
¼ S 24
¼ S 25
1962

from which new bearing trees:

A hemlock, 13 ins. diam., bears N. 21° W., 69 lks. dist.,
mkd. ¼ S24 BT.

A yew, 22 ins. diam., bears S. 42° E., 68 lks. dist.,
mkd. ¼ S25 BT.

The cor. of secs. 13, 14, 23 and 24, determined at record
bearing and distance from the three remaining original
bearing trees:

A rotted hemlock stump, bears N. 22° E., 59 lks. dist.,
with scribe marks 8 S visible on opened blaze.

A fir, 60 ins. diam., bears S. 32½° W., 39 lks. dist.,
with no marks remaining on sawed out face.

A hemlock, 27 ins. diam., bears N. 58° W., 47 lks. dist.,
with no mark visible on partially opened blaze.

and two trees not of record:

A hemlock, 35 ins. diam., bears S. 51° E., 109 lks. dist.,
with scribe marks S13 BT 473 visible on open blaze.

A sawed fir stump, 50 ins. diam., bears S. 12° E., 55 lks.
dist., with scribe marks S24 BT visible on open blaze.