

Dependent Resurvey, Subdivisional Lines. T. 24 S., R. 1 W.

CHAINS

A cedar, 30 ins. diam., bears S. 43° W., 14 lks. dist., with healed blaze.

A sugar pine, 37 ins. diam., bears N. 53° W., 117 lks. dist., with healed blaze. (Record calls for a fir)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 24 S R 1 W
S 5 S 4
S 8 S 9
1963

N. $88^{\circ} 41'$ W., bet. secs. 5 and 8, marking and blazing the true line.

Ascend 43 ft. along S. slope, through heavy timber and dense undergrowth.

- 9.60 Top of ascent, slopes S. 15° E.; desc. 36 ft. over SW slope.
- 11.06 Creek, 1 lk. wide, course SE.; asc. 252 ft. along S. slope.
- 22.99 Creek, 2 lks. wide, course SE.; asc. 108 ft. over SE. slope
- 26.98 Spur, slopes S. 30° E.; desc. 66 ft. over SW. slope.
- 30.80 Ravine, drains S.; asc. 12 ft. over SE. slope.
- 32.29 Spur, slopes S. 20° E.; desc. 45 ft. over SW. slope.
- 35.39 Ravine, drains S.; asc. 53 ft. along S. slope.
- 40.81 The $\frac{1}{4}$ sec. corn. of secs. 5 and 8, monumented with the original basalt stone, 20 x 8 x 8 ins., firmly set, 4 ins. in the ground, marked $\frac{1}{4}$ on north face, from which the original bearing trees:
- A fir, 35 ins. diam., bears N. 49° E., 47 lks. dist., with healed blaze.
- A fir, 26 ins. diam., bears S. 25° W., 19 lks. dist., with healed blaze.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.
- | |
|-------------------|
| T 24 S R 1 W |
| $\frac{1}{4}$ S 5 |
| S 8 |
| 1963 |
- Deposit corner stone alongside the iron post.
- S. $89^{\circ} 43'$ W., beginning new measurement.
- Ascend 23 ft. along S. slope, through heavy timber and dense undergrowth.