

CHAINS	Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 5 W.
	<p>from which the original bear trees</p> <p>A stump hole, bears N. <math>70\frac{1}{2}^{\circ}</math> E., 65 lks. dist.</p> <p>A rotted oak stump, size indeterminate, bears S. <math>34^{\circ}</math> E., 37 lks. dist., with no marks remaining.</p> <p>A white oak, 26 ins. diam., bears S. <math>81^{\circ}</math> W., 229 lks. dist., with fragmentary scribe marks visible on partially opened blaze.</p> <p>An oak stump, 26 ins. diam., lies on the ground, near a point which bears N. <math>40^{\circ}</math> W., 97 lks. dist., with axe marks visible on decayed blaze.</p> <p>and the county Surveyors bearing trees</p> <p>A fir, 9 ins. diam., bears N. <math>52\frac{1}{2}^{\circ}</math> E., 58 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A fir, 9 ins. diam., bears S. <math>30^{\circ}</math> E., <math>26\frac{1}{2}</math> lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A fir, 19 ins. diam., bears S. <math>23^{\circ}</math> W., 41 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A white oak, 10 ins. diam., bears N. <math>70\frac{1}{4}^{\circ}</math> W., 65 lks. dist., with scribe marks T25S R5W S9 CS BT visible on unhealed blaze.</p> <p>North, bet. secs. 9 and 10, marking and blazing the true line.</p> <p>Ascend 48 ft. over S. slope, across logged area through dense undergrowth.</p> <p>4.20 Spur, slopes SW.; asc. 100 ft. over SW. slope.</p> <p>20.00 Point for the S <math>\frac{1}{16}</math> sec. cor. of secs. 9 and 10.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 28 ins. in the ground, with brass cap marked</p> <p style="text-align: center;">S <math>\frac{1}{16}</math> S 9   S 10 1962</p> <p>from which</p> <p>A fir, 9 ins. diam., bears S. <math>40\frac{1}{2}^{\circ}</math> E., 25 lks. dist., marked S <math>\frac{1}{16}</math> S10 BT.</p> <p>A fir, 13 ins. diam., bears N. <math>30\frac{1}{2}^{\circ}</math> W., 71 lks. dist., marked S <math>\frac{1}{16}</math> S9 BT.</p> <p>Cor. falls at top of ascent, slopes W.</p> <p>Leave logged area, enter second growth timber, edge bears E. and W.; desc. 29 ft. along W. slope.</p> <p>33.60 Spur, slopes N. <math>10^{\circ}</math> W.; desc. 188 ft. over NE. slope.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 10 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 28 ins. in the ground, with brass cap marked</p>