

## County Surveyor's Record, Douglas County, Oregon

5

CHAINS	<p>Dependent Resurvey, Subdivsional Lines, T. 25 S., R. 5 W.</p> <p>Descend 12 ft. over SW. slope.</p> <p>43.00 Ravine, drains SW.,; asc. 178 ft. over SE. slope.</p> <p>53.30 Spur, slopes S.; desc. 24 ft. over SW. slope.</p> <p>59.97 Point for W 1/16 sec. cor. of secs. 9 and 16.</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 28 ins. in the ground, with brass cap marked</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: center;">S 9</td> </tr> <tr> <td style="text-align: center;">W 1/16</td> <td style="text-align: center;">S 16</td> </tr> <tr> <td></td> <td style="text-align: center;">1962</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. <math>63^{\circ}</math> E., 14 lks. dist., marked W 1/16 S9 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. <math>27^{\circ}</math> E., 17 lks. dist., marked W 1/16 S16 BT.</p> <p>Ascend 146 ft. over broken SE. slope.</p> <p>79.96 The cor. of secs. 8,9, 16, and 17, perpetuated by the Douglas County Surveyor in 1960, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above the ground, with brass cap marked</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="4" style="text-align: center;">County Surveyors Office</td> </tr> <tr> <td colspan="4" style="text-align: center;">T 25 S. R 5 W</td> </tr> <tr> <td></td> <td style="text-align: center;">S 8</td> <td style="text-align: center;">S 9</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">S 17</td> <td style="text-align: center;">S 16</td> <td></td> </tr> <tr> <td colspan="4" style="text-align: center;">1960</td> </tr> </table> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A rotted oak stump, 18 ins. diam., bears N. <math>57\frac{1}{2}^{\circ}</math> E., 100 lks. dist., with scribe marks T25S R5W S9 BT visible in negative on the overgrowth.</p> <p style="padding-left: 40px;">A stump hole, bears S. <math>38\frac{1}{2}^{\circ}</math> W., 30 lks. dist. The trunk of the original BT., an oak, 30 ins. diam., is lying down hill from the stump hole, with scribe marks T2 R5W visible in negative on the overgrowth. (Record 40 lks.)</p> <p style="padding-left: 40px;">A down and rotted oak, size indeterminate, bears N <math>69^{\circ}</math> W., 36 lks. dist., with axe marks but no scribe marks visible on decayed blaze.</p> <p>and the County Surveyors bearing trees</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. <math>5\frac{1}{2}^{\circ}</math> E., 90 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. <math>78^{\circ}</math> E., 50 lks. dist., with scribe marks T25S R5W S16 CS BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. <math>42^{\circ}</math> W., 177 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. <math>71\frac{1}{2}^{\circ}</math> W., 79 lks.</p>		S 9	W 1/16	S 16		1962	County Surveyors Office				T 25 S. R 5 W					S 8	S 9			S 17	S 16		1960			
	S 9																										
W 1/16	S 16																										
	1962																										
County Surveyors Office																											
T 25 S. R 5 W																											
	S 8	S 9																									
	S 17	S 16																									
1960																											