

County Surveyor's Record, Douglas County, Oregon

7

CHAINS

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 5 W.

A clump of madrone shoots, bears S. $72-3/4^{\circ}$ W., 45 lks. dist.

and the County Surveyor's 1960 bearing trees

A black oak, 34 ins. diam., bears S. 8° E., 115 lks. dist., with scribe marks $\frac{1}{4}$ S9 CS BT visible on unhealed blaze.

A white oak, 13 ins. diam., bears N. 74° W., 107 lks. dist., with scribe marks $\frac{1}{4}$ S8 CS BT visible on unhealed blaze.

N. 0° 08' W., beginning new measurement.

Descend 247 ft. over general NW. slope.

- 2.10 Power line, 3 wires, bears E. and W.
- 8.00 Telephone line, 3 wires, bears N. 60° E. and S. 60° W.
- 13.56 From this point, an iron pipe, 1 in. diam., projecting 4 ins. above the ground, bears East, $22\frac{1}{2}$ lks. dist.
- 20.80 Paved highway, 50 lks. wide, bears NE. and SW.
- 26.20 Center line of railroad, bears NE. and SW.; thence across mill pond, by triangulation.
- 33.90 North edge of mill pond, bears N. 70° E. and S. 70° W.; thence across level graded field.
- 34.80 Power line, 3 wires, bears N. 70° E. and S. 70° W.
- 35.40 Paved road, 40 lks. wide, bears N. 70° E. and S. 70° W.
- 40.21 The cor. of secs. 4, 5, 8, and 9, monumented by A.R. Evans, Registered Engineer, in 1950, with an iron post, 1 in. diam., projecting 1 in. above the ground, set in concrete, with brass cap marked

T 25 S

$\frac{5}{8} | \frac{4}{9}$

RE 2741

R 5 W

The point was monumented at the position perpetuated by the Douglas County Surveyor in 1917, with a stone, 24 x 18 x 10 ins., the position of which was determined at record bearing and distance from the original northwest bearing tree, which has since been destroyed.

from which a bearing tree marked by A.R. Evans in 1950

An elm, 31 ins. diam., bears S. $63\frac{1}{2}^{\circ}$ E., 486 lks. dist., with scribe marks T25S R5W S9 CS BT visible on partially healed blaze.

Raise a mound of stone, 4 ft. base, 6 ins. high, around the iron post.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 89° 05'E., 249 lks. dist., with brass