

County Surveyor's Record, Douglas County, Oregon

CHAINS	Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 5 W.
	cap marked T25S R5W S9 RM with an arrow pointing to the corner.
	An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 34° 50' E., 135 lks. dist., with brass cap marked T25S R5W S4 RM with an arrow pointing to the corner.
	Land, mountainous. Soil, clay loam. Timber, fir, cedar, oak, and madrone, undergrowth, poison oak, blackberry, chinquapin, madrone, arrowwood, wild rose, and hazel.
	From the cor. of secs. 3, 4, 9, and 10. N. 89° 23' W., bet. secs. 4 and 9. Ascend 14 ft. over SE. slope, through scattering timber and light undergrowth.
6.20	Ridge, bears N. 70° E. and S. 70° W.; desc. 443 ft. over broken NW. slope.
34.00	Creek, 5 lks. wide, course NW.; asc. 65 ft. over NE. slope.
35.60	Dirt road, 15 lks. wide, bears NW. and SE.
39.99	The ¼ sec. cor. of secs. 4 and 9, monumented with an iron bolt, set in a concrete post, 6 ins. diam., projecting 6 ins. above the ground from which the only remaining original bearing tree An oak snag, 17 ins. diam., bears N. 21½° E., 10 lks. dist., with no marks remaining on decayed blaze. and a bearing tree of which I have no record An oak, 23 ins. diam., bears N. 41° E., 31 lks. dist., with scribe marks ¼ S visible on partially healed blaze. At the corner point Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap marked T 25 S R 5 W ¼ S 4 S 9 1962 from which An oak, 8 ins. diam., bears S. 17° W., 21 lks. dist., marked ¼ S9 BT. Deposit the concrete post alongside the iron post. N. 89° 12' W., beginning new measurement. Descend 109 ft. over general NW. slope.
6.50	Telephone line, 3 wires, bears N. 60° E. and S. 60° W.
8.20	Dirt road, 15 lks. wide, bears N. 45° E. and S. 40° W.
10.40	Power line, 2 wires, bears N. 80° W. and S. 80° E.