

County Surveyor's Record, Douglas County, Oregon

9.

CHAINS Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 5 W.12.60 Power line, 3 wires, bears N. 10° E. and S. 10° W.

13.20 Paved highway, 45 lks. wide, bears N. and S.

14.10 Center line of railroad, bears N. and S.; thence across
lumber yard.

40.04 The cor. of secs. 4, 5, 8, and 9.

Land, E. $\frac{1}{2}$ mile mountainous; W. $\frac{1}{2}$ mile nearly level.
Soil, clay loam.Timber, fir, oak, maple, cedar, and madrone; undergrowth,
poison oak, wild rose, madrone, chinquapin, oak, and
blackberry.Subdivision of Sec. 9, T. 25 S., R. 5 W.The following subdivision of section was executed in con-
formity with legal surveying practice. The record of
true line notes only, set forth in the following field
notes.From the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.

North, on the N. and S. center line of sec. 9.

Ascend 53 ft. over SW. slope, through heavy timber and
light undergrowth.5.40 Ravine, drains S. 10° W.; asc. 194 ft. over SE. slope.19.98 Point for the center S $1/16$ sec. cor. of sec. 9.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in
the ground, with brass cap marked
$$\begin{array}{c} C \\ S\ 1/16 \left| S\ 9 \\ C \\ 1962 \end{array}$$

from which

A fir, 14 ins. diam., bears S. 75° E., $6\frac{1}{2}$ lks.
dist., marked CS $1/16$ S9 BT.A fir, 14 ins. diam., bears N. 33° W., 10 lks.
dist., marked CS $1/16$ S9 BT.

Ascend 48 ft. over SE. slope.

26.00 Ridge, bears NE. and SW.; desc. 198 ft. over NW. slope.

39.96 Point for the center $\frac{1}{4}$ sec. cor. of sec. 9, at intersec-
tion with the E. and W. center line.Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins.
in the ground, with brass cap marked
$$\begin{array}{c} C\ \frac{1}{4}\ S9 \\ 1962 \end{array}$$

from which

A fir, 17 ins. diam., bears N. 15° E., 22 lks.