

CHAINS	Subdivision of Section 9, T. 25 S., R. 5 W.
	slope.
31.80	Ravine, drains S.; asc. 137 ft. over SE. slope.
39.96	The center S 1/16 sec. cor. of sec. 9.
	From the W 1/16 sec. cor. of secs. 9 and 16.
	N. 0° 03' W., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 9.
	Ascend 252 ft. over SE. slope, through heavy timber and light undergrowth.
19.99	Point for the SW 1/16 sec. cor. of sec. 9 at intersection with the E. and W. center line of the SW $\frac{1}{4}$.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap marked
	SW 1/16 S9 1962
	from which
	A fir, 21 ins. diam., bears S. 88 $\frac{1}{2}$ ° E., 31 $\frac{1}{2}$ lks. dist., marked SW 1/16 S9 BT.
	A fir, 23 ins. diam., bears N. 71° W., 71 lks. dist. marked SW 1/16 S9 BT.
	Ascend 5 ft over SE. slope.
20.70	Ridge, bears E. and W.; desc. 341 ft. over NE. slope.
39.93	The center W 1/16 sec. cor. of sec. 9.
	From the center S 1/16 sec. cor. of sec. 9.
	N. 89° 23' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 9.
	Ascend 21 ft. over SE. slope, through heavy timber and light undergrowth.
2.70	Spur, slopes S.; desc. 42 ft. over SW. slope.
6.70	Ravine, drains S.; asc. 84 ft. over SE. slope.
16.40	Ridge, bears N. 70° E. and W.; asc. 52 ft. along ridge top.
20.02	The SW 1/16 sec. cor. of sec. 9. Ascend 25 ft. along ridge top.
22.10	Leave ridge, bears S. 50° W. and East; desc. 86 ft. over NW slope.
25.30	Ravine, drains N.; asc. 31 ft. over NE. slope.
26.80	Spur, slopes N.; desc. 414 ft. over NW. slope.
38.90	Power line, 3 wires, bears N. 20° E. and S. 20° W.
40.00	The S 1/16 sec. cor. of secs. 8 and 9.