

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivsional Lines, T. 23 S., R. 7 W.

CHAINS	Land, mountainous. Soil, sandy clay loam and rock outcrops. Timber, fir, hemlock, cedar, maple, alder, chinquapin, and madrone; undergrowth, vine maple, hazel, arrowwood, salmonberry, huckleberry, salal, poison oak, and fern.
	From the cor. of secs. 21, 22, 27, and 28.
	N. 89° 51' W., bet. secs. 21 and 28.
	Descend 59 ft. over SW. slope, through medium timber and undergrowth.
4.20	Ravine, drains S. 30° W.; asc. 56 ft. over SE. slope.
6.75	Spur, slopes S.; desc. 150 ft. over SW. slope.
16.30	Ravine, drains S. 20° W.; asc. 142 ft. over broken SE. slope.
23.15	Top of ascent, slopes S.; desc. 152 ft. over general SW. slope.
30.90	Ravine, drains S.; asc. 109 ft. over precipitous E. slope.
34.80	Spur, slopes S.; desc. 300 ft. over general W. slope.
41.05	The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, reestablished and recorded by F.E. Waggoner, Registered Land Surveyor No. 149, in 1955, monumented with a sandstone, 14 x 12 x 8 ins. firmly set 8 ins. in the ground, marked $\frac{1}{4}$ on the W. face, and a steel rod, $\frac{5}{8}$ in. diam., 18 ins. long, firmly set 14 ins. in the ground, from which the Waggoner bearing trees: <p style="margin-left: 40px;">A fir snag, 40 ins. diam., bears N. 1$\frac{1}{2}$° W., 73 lks. dist., with scribe marks S21 BT visible on unhealed blaze.</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears S. 10° E., 36$\frac{1}{2}$ lks. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked</p> <div style="text-align: center;"> $\begin{array}{r} \frac{1}{4} \text{ S } 21 \\ \frac{1}{4} \text{ S } 28 \\ \text{T } 23 \text{ S } \text{R } 7 \text{ W} \\ 1963 \end{array}$ </div> <p>from which a new bearing tree</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears N. 42$\frac{1}{2}$° W., 39 lks. dist., marked $\frac{1}{4}$ S21 BT.</p> <p>Deposit sandstone <u>and steel rod alongside</u> the iron posts. N. 89° 51' W., beginning new measurement.</p> <p>Descend 75 ft. over NW. slope.</p>
4.30	Ravine, drains S. 85° W.; desc. 165 ft. along general S. slope.
12.05	Maupin Road, 20 lks. wide, gravelled, bears N. 35° W.