

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivsional Lines, T. 23 S., R. 7 W.

CHAINS
40.37

The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, reestablished and recorded by F.E. Waggoner, Registered Land Surveyor, No. 149, in 1955, monumented with a steel rod, $\frac{5}{8}$ in. diam., 18 ins. long, firmly set 14 ins. in the ground, from which the Waggoner bearing tree:

A fir, 16 ins. diam., bears N. 47° E., 93 lks. dist., with a healed blazed breast high.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 20 \mid \text{S } 21 \\ \text{T } 23 \text{ S } \mid \text{R } 7 \text{ W} \\ 1963 \end{array}$$

from which a new bearing tree

A double white oak, 5 ins. diam., bears N. $1\frac{1}{4}^{\circ}$ W., 144 lks. dist., marked $\frac{1}{4}$ S20 BT.

Deposit the steel rod alongside the iron post.

N. 1° 19' E., beginning new measurement.

Ascend 145 ft. over general S. slope.

10.70 Ridge, bears E. and W.; desc. 87 ft. over general N. slope.

20.185 The N $\frac{1}{16}$ sec. cor. of secs. 20 and 21, established and recorded by F.E. Waggoner, Registered Land Surveyor No. 149, in 1955, monumented with a steel rod, $\frac{5}{8}$ in. diam., 18 ins. long, firmly set 14 ins. in the ground, from which the Waggoner bearing tree:

A fir, 14 ins. diam., bears S. 55° E., 49 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{N } \frac{1}{16} \\ \text{S } 20 \mid \text{S } 21 \\ 1963 \end{array}$$

from which a new bearing tree:

A fir, 4 ins. diam., bears S. 72° W., 11 lks. dist., marked N $\frac{1}{16}$ S20 BT.

Deposit the steel rod alongside the iron post.

The cor. falls at foot of descent, slopes NE.; asc. 186 ft. along broken E. slope.

36.10 Top of ascent, slopes NE.; desc. 33 ft. over NW. slope.

40.37 The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above ground, marked and witnessed as described in the official record.