

County Surveyor's Record, Douglas County, Oregon

7

Subdivision of Section 21, T. 23 S., R. 7 W.

CHAINS	
	<p>from which</p> <p>A white oak, 9 ins. diam., bears N. 7° W., 88 lks. dist., marked C$\frac{1}{4}$ S21 BT.</p> <p>A fir, 7 ins. diam., bears S. 4° W., 23 lks. dist., marked C$\frac{1}{4}$ S21 BT.</p> <p>Ascend 4 ft. over SW. slope.</p>
41.50	Ridge, bears NW. and SE.; desc. 280 ft. over general N. slope, changing to NE. slope.
57.50	Creek, 8 lks. wide, course N. 40° W.; asc. 26 ft. over SW. slope.
59.05	Dirt access road, 20 lks. wide, bears N. 35° W. and S. 35° E.
59.645	Point for the center N 1/16 sec. cor. of sec. 21. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked <div style="text-align: center;"> C N 1/16 S 21 C 1963 </div>
	<p>from which</p> <p>A cedar, 23 ins. diam., bears N. 80° E., 93 lks. dist., marked CN 1/16 S21 BT.</p> <p>A fir, 8 ins. diam., bears S. 24° E., 89 lks. dist., marked CN 1/16 S21 BT.</p> <p>Ascend 40 ft. over SW. slope.</p>
64.90	Dirt access road, 20 lks. wide, bears N. 80° W. and S. 80° E.
66.50	Top of ascent slopes W.; desc. 103 ft. over general N. slope.
72.50	Creek, 10 lks. wide, course N. 50° E.; asc. 103 ft. over SE. slope.
79.07	The $\frac{1}{4}$ sec. corner of secs. 16 and 21, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, marked and witnessed as described in the official record.
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.</p> <p>N. 89° 31' W., along the E. and W. center line of sec. 21.</p> <p>Ascend 130 ft. over E. slope, through scattering timber and dense undergrowth.</p>
3.60	Spur, slopes N. 25° W.; desc. 288 ft. over SW. slope.
26.50	Creek, 2 lks. wide, course NW.; asc. 222 ft. over NE. slope.
36.25	Ridge, bears S. 15° E. and N. 20° W.; desc. 47 ft. over SW. slope.