

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 21, T. 23 S., R. 7 W.

CHAINS

- 41.28 The center $\frac{1}{4}$ sec. cor. of sec. 21.
Descend 206 ft. over SW. slope.
- 47.50 Enter nearly open pasture land, edge bears NW. and SE.
- 59.80 Enter light timber and dense undergrowth, edge bears N. and S.
- 60.60 Ravine, drains S. 70° W.; asc. 14 ft. over SE. slope.
- 61.43 Point for the center W $\frac{1}{16}$ sec. cor. of sec. 21.
Set an iron post; 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

W $\frac{1}{16}$
C-----C
S 21
1963

from which

A white oak, 9 ins. diam., bears N. 54° W., 29 lks. dist., marked CW $\frac{1}{16}$ S21 BT.

A fir, 19 ins. diam., bears S. 18° E., 49 lks. dist., marked CW $\frac{1}{16}$ S21 BT.

Ascend 30 ft. over SE. slope.

- 63.50 Top of ascent, slopes S.; desc. 258 ft. over SW. slope.
- 75.90 Ravine, drains S. 20° W.; asc. 139 ft. over SE. slope.
- 81.58 The $\frac{1}{4}$ sec. cor. of secs. 20 and 21.

From the center N $\frac{1}{16}$ sec. cor. of sec. 21.N. $89^{\circ} 01'$ E., along the E. and W. center line of the NE $\frac{1}{4}$ of sec. 21, on mean bearing.

Ascend 344 ft. over SW. slope, through scattering timber and undergrowth.

- 29.80 Fence, 3 strand barbed wire, bears N. and S.
- 32.00 Spur, slopes N.; desc. 256 ft. over precipitous E. slope.
- 36.62 Point for the special meander cor. of sec. 21 at intersection with the adjusted meander line on the left bank of the Umpqua River.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked

N S

21
1963 N
 SMC

from which

A fir, 11 ins. diam., bears N. $47-3/4^{\circ}$ W., 7 lks. dist., marked SMC S21 BT.