

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 9 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked

$$\begin{array}{r} T\ 30\ S\ R\ 9\ W \\ S\ 7\ | S\ 8 \\ S\ 18\ | S\ 17 \\ 1962 \end{array}$$

from which new bearing trees:

A cedar, 11 ins. diam., bears N.  $27\frac{1}{2}^{\circ}$  E., 35 lks. dist., marked T30S R9W S8BT.

A cedar, 13 ins. diam., bears S.  $38^{\circ}$  E., 239 lks. dist., marked T30S R9W S17BT.

A fir, 13 ins. diam., bears S  $57^{\circ}$  W., 121 lks. dist., marked T30S R9W S18BT.

A fir, 33 ins. diam., bears N.  $71^{\circ}$  W., 87 lks. dist., marked T30S R9W S7 BT.

N.  $0^{\circ}$  09' W., bet. secs. 7 and 8, marking and blazing the true line.

Ascend 785 ft. over SW. slope, through logged area.

39.62

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 8, monumented with the original corner tree, a down and rotted cedar, 8 ins. diam., with scribe marks  $\frac{1}{4}$  visible on opened blaze, from which the original bearing trees:

A down cedar, 8 ins. diam., bears S.  $72^{\circ}$  E., 39 lks. dist., with scribe marks  $\frac{1}{4}$  S BT visible on unhealed blaze.

A down and rotted fir, 30 ins. diam., bears S.  $40\frac{1}{2}^{\circ}$  W., 34- $\frac{3}{4}$  lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, with brass cap marked

$$\begin{array}{r} \frac{1}{4} \\ S\ 7\ | S\ 8 \\ T\ 30\ S\ | R\ 9\ W \\ 1962 \end{array}$$

from which new bearing trees:

A cedar, 27 ins. diam., bears N.  $49\frac{1}{2}^{\circ}$  E., 98 lks. dist., marked  $\frac{1}{4}$  S8 BT.

A fir, 15 ins. diam., bears S.  $40^{\circ}$  W., 101 lks. dist., marked  $\frac{1}{4}$  S7 BT.

Deposit the remains of original corner tree alongside the iron post.

N.  $0^{\circ}$  25' W., beginning new measurement.

Ascend 15 ft. over SW. slope, through old logged area.