

Dependent Resurvey, Subdivisional Lines, T. 30 S., R. 9 W.

CHAINS

SE. slope.

41.44 The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., re-established by Bushey in 1893, determined at record bearing and distance from the 1893 bearing trees:

A fir, 28 ins. diam., bears N. 7° E., 42 lks. dist., with scribe marks O W visible on partly opened blaze.

A fir, 36 ins. diam., bears S. 79° E., 29½ lks. dist., with healed blaze.

A fir, 24 ins. diam., bears S. 39½° W., 49 lks. dist., with healed blaze.

A fir, 28 ins. diam., bears N. 60° W., 34 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

*Fd. ok 1/84
R. G. Bushey
1197-9*

T 30 S
R 10 W R 9 W
S 1 | S 6
S 12 | S 7
1962

Land, mountainous.
Soil, sandy clay.
Timber, fir, hemlock, cedar, chinquapin, and alder; undergrowth, fern, rhododendron, Oregon grape, vine maple, huckleberry, and bunch grass.

From the cor. of secs. 5, 6, 7, and 8.

N. 0° 17' W., bet. secs. 5 and 6.

Ascend 60 ft. over S. slope, through scattering second growth timber and dense reproduction.

7.30 Ridge, and dirt road, 15 lks. wide, bears N. 85° E., and S. 85° W.; desc. 195 ft. over NW. slope.

19.85 Ravine, drains N. 30° E.; asc. 7 ft. along E. slope.

23.55 Top of ascent; slopes E.; desc. 286 ft. over NE. slope.

34.55 Creek, 2 lks. wide, course N. 35° W.; desc. 74 ft. over NW. slope.

40.44 The ¼ sec. cor. of secs. 5 and 6, determined at record bearing and distance from the remaining original bearing tree, falls in a creek, 25 lks. wide, course W., where it is impracticable to establish a standard monument. The original bearing tree,

A down fir, 20 ins. diam., bears S. 36½° E., 38-¾ lks. dist., with fragmentary scribe marks visible on opened blaze.

At the corner point

Drive a steel rod, 40 ins. long, 5/8 in. diam., 28 ins. in the creek bed to solid rock, from which new bearing trees and a reference monument: