

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 31 S., R. 8 W.

CHAINS

A fir, 50 ins. diam., bears S. 36° E., 80 lks. dist., with healed blaze.

A fir, 33 ins. diam., bears S. 38° W., 13 lks. dist., with a healed blaze.

A fir, 62 ins. diam., bears N. 15° W., 58 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S	
R 9 W R 8 W	
S 25	S 30
S 36	S 31

1960

from which a new bearing tree

A fir, 10 ins. diam., bears N. 73° E., 58 lks. dist., mkd. T31S R8W S30 BT.

Deposit local cor. marker alongside iron post.

N. 0° 22'E., bet. secs. 25 and 30, marking and blazing the true line.

Desc. 210 ft. over NW. slope, through logged area, timber to W.

12.70 Creek, 3 lks. wide, course N. 70° W.; asc. 75 ft. over SW. slope.

19.63 Point for the S $1/16$ sec. cor. of secs. 25 and 30.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

S $1/16$	
S 25	S 30
R 9 W	R 8 W
T 31 S	

1962

from which

A fir, 25 ins. diam., bears N. 83° E., 109 lks. dist., mkd. S $1/16$ S30 BT.

A fir, 42 ins. diam., bears N. 15° W., 106 lks. dist., mkd. S $1/16$ S25 BT.

19.65 Spur slopes N. 70° W.; desc. 360 ft. over NE. slope.

27.90 Dirt road, 15 lks. wide, bears E. and W.

39.26 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, perpetuated with an iron pipe, 1 in. diam., firmly set, protruding 4 ins. above the ground, from which the original bearing trees:

A fir, 22 ins. diam., bears N. 80° E., 40 lks. dist., mkd. with healed blaze and cruiser marks (record, N. 42° E., 16 lks. dist.)

A fir, 33 ins. diam., bears S. 30° W., 5 lks.