

Dependent Resurvey, Portion of W. Bdy., T. 31 S., R. 8 W.

## CHAINS

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, hemlock, cedar, oak, madrone and pine;  
undergrowth, salal, vine maple, chinquapin, live oak,  
hazel, rhododendron, ferns and vines.

N. 0° 06' E., bet. secs. 19 and 24.

Ascend 165 ft. over SW. slope, through old logged area,  
timber W.

5.45 Spur, slopes S. 20° E.; asc. 105 ft. over SE. slope.

16.60 Draw, drains S. 25° E.; asc. 175 ft. over SW. slope.

20.00 Enter timber; edges bear E. and S.

24.00 Spur, slopes S. 20° E.; asc. 130 ft. over SE. slope.

38.00 Spur, slopes S. 60° W.; desc. 10 ft. over NW. slope.

40.09 The  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, determined at  
record bearing and distance from the remaining original  
bearing tree:

A fir, 32 ins. diam., bears N. 71° E., 72 lks.  
dist., illegible scribe marks visible on  
opened face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

$\frac{1}{4}$   
S 24 | S 19  
R 9 W | R 8 W  
T 31 S  
1962

from which new bearing trees

A fir, 12 ins. diam., bears N.  $18\frac{1}{4}$ ° E.,  $11\frac{1}{2}$  lks.  
dist., mkd.  $\frac{1}{4}$  S19 BT.

A fir, 12 ins. diam., bears N.  $86\frac{1}{2}$ ° W., 63 lks.  
dist., mkd.  $\frac{1}{4}$  S24 BT.

N. 0° 14' W., beginning new measurement.

7.05 Spur, slopes W.; desc. 70 ft. over NW. slope.

12.00 Draw, drains S. 40° W.; asc. 80 ft. along W. slope.

23.30 Spur, slopes S. 40° W.; desc. 70 ft. over NW. slope.

28.00 Draw; drains S. 30° W.; asc. 35 ft. over SE. slope.

39.63 The cor. of secs. 13, 18, 19, and 24, determined at  
record distance from the remaining original bearing  
trees:

A fir, 22 ins. diam., bears N. 54° E., 12 lks.  
dist., scribe marks visible on partially healed  
blaze. (Record bearing, N. 64° E.)