

Dependent Resurvey, Portion of W. Bdy., T. 31 S., R. 8 W.

CHAINS

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 13 \text{ | S } 18 \\ \text{R } 9 \text{ W | R } 8 \text{ W} \\ \text{T } 31 \text{ S} \\ 1962 \end{array}$$

N. 0° 14' E., beginning new measurement.

Descend 23 ft. along broken W. slope, through logged area.

34.50 Dry creek, 3 lks. wide, course W.; asc 50 ft. along broken W. slope.

40.35 The cor. of secs. 7, 12, 13, and 18, determined from the remains of the original bearing trees:

A rotted fir stump, 27 ins. diam., bears N. $50\frac{1}{2}^{\circ}$ E., 13 lks. dist., no marks remaining. (Record bearing, N. 55° E.)

A cedar, 30 ins. diam., bears S. $30\frac{1}{2}^{\circ}$ E., 61 lks. dist., scribe marks S18 visible on opened blaze. (Record bearing, S. 52° E.)

A fir, 50 ins. diam., bears S. 30° W., 31 lks. dist., old axe marks visible. (Record distance, 28 lks.)

A rotted fir stump,, bears N. 75° W., 34 lks. dist., no marks remaining. (Records distance, 30 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{T } 31 \text{ S} \\ \text{R } 9 \text{ W | R } 8 \text{ W} \\ \text{S } 12 \text{ | S } 7 \\ \text{S } 13 \text{ | S } 18 \\ 1962 \end{array}$$

from which new bearing trees

A fir, 21 ins. diam., bears N. 88° E., 29 lks. dist., mkd. T31S R8W S7 BT.

A fir, 16 ins. diam., bears S. $42\frac{1}{2}^{\circ}$ E., 65 lks. dist., mkd. T31S R8W S18 BT.

A fir, 26 ins. diam., bears S. 65° W., 82 lks. dist., mkd. T31S R9W S13 BT.

A fir, 17 ins. diam., bears N. 55° W., 35 lks. dist., mkd. T31S R9W S12 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, pine, oak, madrone and chinquapin; undergrowth, salal, vine maple, hazel, rhododendron, poison oak, ferns and vines.