

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 31 S., R. 8 W.

CHAINS

pine, undergrowth, salal, huckleberry, salmonberry,  
live oak, hazel, rhododendron, ferns and vines.

Dependent Resurvey of a Portion of the N. Bdy.  
of T. 31 S., R. 8 W., Willamette Meridian, Oregon  
(Restoring the 1882 survey by William H. Byars)

From the cor. of Tps. 30 and 31 S., Rs. 8 and 9 W.,  
heretofore described.

N.  $87^{\circ} 49'$  E., bet. secs. 6 and 31, marking and blazing  
the true line.

Descend 5 ft. over E. slope, through heavy timber and  
moderate undergrowth.

3.20 Spur, slopes N.  $70^{\circ}$  E.; desc. 510 ft. over SE. slope.

18.90 Creek, 2 lks. wide, course N.; land nearly level.

21.45 Creek, 2 lks. wide, course N.  $15^{\circ}$  E., curving NW.;  
leave bottomland, asc. 75 ft. over broken NW. slope.

26.90 Spring branch, 1 lk. wide, course N.  $10^{\circ}$  W.; asc. 185  
ft. over broken NW. slope.

34.70 Spur, ridge, slopes N.; desc. 165 ft. over E. slope.

45.14 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, at propor-  
tionate distance; there is no remaining evidence of the  
original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 30 S R 8 W  
 $\frac{1}{4}$   $\frac{S 31}{S 6}$   
T 31 S  
1962

from which

A cedar, 35 ins. diam., bears N.  $16^{\circ}$  W., 49 lks.  
dist., mkd.  $\frac{1}{4}$  S31 BT.

A fir, 45 ins. diam., bears South, 7 lks. dist.,  
mkd.  $\frac{1}{4}$  S6 BT.

Descend 335 ft. over E. slope.

71.00 Creek, 10 lks. wide, course N.  $5^{\circ}$  E.; asc. 440 ft. over  
W. slope.

80.75 Spur, slopes N.; desc. 50 ft. over E. slope.

82.67 The cor. of secs. 5, 6, 31, and 32, determined at record  
bearing and distance from the remaining original  
bearing trees:

A fir, 62 ins. diam., bears S.  $16^{\circ}$  E., 40 lks.  
dist., mkd. T31S R8W S5 BT on bark blaze.

A fir snag, 10 ins. diam., bears N.  $40^{\circ}$  W., 8 lks.  
dist., mkd. W on open blaze.

At the corner point