

County Surveyor's Record, Douglas County, Oregon

11

Dependent Resurvey, Portion of N. Bdy., T. 31 S., R. 8 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S R 8 W
 $\frac{S 31}{S 6} | \frac{S 32}{S 5}$
 T 31 S
 1962

from which new bearing trees

A fir, 23 ins. diam., bears N. 85° E., 66 lks. dist., mkd. T30S R8W S32 BT.

A fir, 15 ins. diam., bears S. 42° E., 25 lks. dist., mkd. T31S R8W S5 BT.

A cedar, 6 ins. diam., bears S. 89° W., 43 lks. dist., mkd. T31S R8W S6 BT.

A fir, 47 ins. diam., bears N. $21\frac{1}{2}^{\circ}$ W., 43 lks. dist., mkd. T30S R8W S31 BT on bark blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, madrone, chinquapin, oak, pine and maple; undergrowth, salal, rhododendron, vine maple, huckleberry, poison oak, live oak, ferns and vines.

N. 86° 14' E., bet. secs. 5 and 32.

Descend 65 ft. over broken N. slope, through heavy timber and moderate undergrowth.

11.00 Creek, 1 lk. wide, course N.; asc. 40 ft. along broken N. slope.

23.70 Creek, 3 lks. wide, course N. 20° W.; asc. 345 ft. over W. slope.

38.88 The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, determined at record bearing and distance from the remaining original bearing tree:

A fir, 27 ins. diam., bears N. 54° W., 10 lks. dist., mkd. $\frac{1}{4}$ on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S R 8 W
 $\frac{\frac{1}{4} S 32}{S 5}$
 T 31 S
 1960

from which new bearing trees

A fir, 19 ins. diam., bears N. 30° W., 49 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

A fir, 15 ins. diam., bears S. 77° E., 20 lks. dist., mkd. $\frac{1}{4}$ S5 BT.