

County Surveyor's Record, Douglas County, Oregon

13

Dependent Resurvey, Portion of N. Bdy., T. 31 S., R. 8 W.

CHAINS

20.00

Enter logged area; edges bear S. and E.

39.71

The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, determined at record bearing and distance from the original bearing trees:

A fir, 20 ins. diam., bears N. 12° E., 21 lks.
dist., mkd. $\frac{1}{4}$ S on bark blaze. Remarkd $\frac{1}{4}$ S33
BT.

A fir, 22 ins. diam., bears S. 6° W., 14 lks.
dist., mkd. $\frac{1}{4}$ S on bark blaze. Remarkd $\frac{1}{4}$ S4
BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S R 8 W

$$\frac{1}{4} \frac{S 33}{S 4}$$

T 31 S

1962

Land, mountainous.

Soil, rocky clay, loam.

Timber, fir, hemlock, cedar, pine, madrone, oak, and chinquapin; undergrowth, salal, hazel, rhododendron, huckleberry, poison oak, ferns and vines.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 31 S., R. 8 W., Willamette Meridian, Oregon
(Restoring the 1883 survey by William H. Byars)

From the cor. of secs. 14, 15, 22, and 23, monumented with a stone, 15 x 12 x 10 ins., firmly set, mkd. with 3 notches on the S. and 2 notches on the E. edges, from which the remaining original bearing trees:

A fir, 30 ins. diam., bears N. 25° E., 10 lks.
dist., mkd. T31S R8W S14 BT on bark blaze.

A down fir, 10 ins. diam., bears S. 60° E., 9 lks.
dist., with a healed blaze.

A fir, 18 ins. diam., bears N. 25° W., 57 lks.
dist., mkd. T31S R8 S15 BT on bark blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in mound of stone, 3 ft. base, to top, with brass cap mkd.

T 31 S R 8 W

$$\frac{S 15 | S 14}{S 22 | S 23}$$

1961

from which new bearing trees:

A fir, 22 ins. diam., bears N. 61° E. 30 lks.
dist., mkd. T31S R8W S14 BT.

A cedar, 10 ins. diam., bears S. 30° E., 57 lks.
dist., mkd. T31S R8W S23 BT.