

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 8 W.

CHAINS	
	<p>A fir, 12 ins. diam., bears S. 50° W., 10 lks. dist., mkd. T31S R8W S22 BT.</p> <p>A cedar, 6 ins. diam., bears N. 79° W., 45 lks. dist., mkd. T31S R8W S15 BT.</p> <p>Deposit original corner stone alongside iron post.</p> <p>N. 0° 14' W., bet. secs. 14 and 15, marking and blazing the true line.</p> <p>Ascend 20 ft. over SW. slope, through heavy timber and moderate undergrowth.</p>
0.50	Spur, slopes S. 35° W.; asc. 35 ft. along W. slope.
6.55	Creek, 3 lks. wide, course SW.; asc. 630 ft. over SE. slope, changing to SW. slope.
24.50	Spur, slopes S. 25° W.; asc. 10 ft. over SW. slope.
33.40	Draw, drains S. 80° W.; asc. 155 ft. over SW. slope.
40.60	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 15, monumented with a granite stone, 14 x 12 x 8 ins., no marks visible, loosely set in a small mound of stone, from which the remaining original bearing tree:</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears S. 75° E., 20 lks. dist. (18 lks. to face), marked with illegible bark scribing on double bark blaze. (Record distance, 18 lks.) Remarkd <math>\frac{1}{4}</math> S14 BT.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 21 ins. in the ground, and in mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \frac{1}{4} \\ S\ 15\   \ S\ 14 \\ T\ 31\ S\   \ R\ 8\ W \\ 1962 \end{array}</math> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 25° W., 72 lks. dist., mkd. <math>\frac{1}{4}</math> S15 BT.</p> <p>Deposit original corner stone alongside iron post.</p> <p>N. 0° 49' E., beginning new measurement.</p> <p>Ascend 200 ft. over SW. slope, through heavy timber and moderate undergrowth.</p>
8.65	Spur, slopes S. 50° E.; desc. 25 ft. along broken E. slope.
10.75	Spur, slopes NE.; desc. 570 ft. over NW. slope, changing to N. sbpe.
33.85	Draw, drains NW.; desc. 195 ft. over NW. slope.
40.15	The cor. of secs. 10, 11, 14, and 15, determined at record distance from the original bearing trees: