

County Surveyor's Record, Douglas County, Oregon

17

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 8 W.

CHAINS	ferns and vines.
	From the cor. of secs. 14, 15, 22 and 23.
	N. $89^{\circ} 34'$ W., bet. secs. 15 and 22.
	Descend 35 ft. over SW. slope, through heavy timber and moderate undergrowth.
1.35	Creek, 4 lks. wide, course S. 20° E.; asc. 430 ft. over SE. slope.
12.85	Spur, slopes S. 20° E.; trail bears N. 20° W. and S. 20° E.; desc. 230 ft. over SW. slope.
18.59	Point for the E $1/16$ sec. cor. of secs. 15 and 22.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{S } 15 \\ \text{E } 1/16 \quad \text{S } 22 \\ \text{T } 31 \text{ S } \text{ R } 8 \text{ W} \\ 1961 \end{array}$
	from which
	A fir, 22 ins. diam., bears N. $30\frac{1}{2}^{\circ}$ E., 25 lks. dist., mkd. E $1/16$ S15 BT.
	A fir, 27 ins. diam., bears S. 42° E., 53 lks. dist., mkd. E $1/16$ S22 BT.
	Descend 380 ft. over SW slope.
29.40	Darby Creek, 10 lks. wide, course S. 10° E.; asc. 285 ft. over NE. slope, changing to N. slope.
37.18	The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, determined at record bearing and distance from the remaining original bearing tree:
	A fir snag, 44 ins. diam., bears South, 60 lks. dist., mkd. $\frac{1}{4}$ S on bark blaze.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{S } 15 \\ \frac{1}{4} \text{ S } 22 \\ \text{T } 31 \text{ S } \text{ R } 8 \text{ W} \\ 1961 \end{array}$
	from which new bear trees
	A fir, 28 ins. diam., bears N. 44° E., 11 lks. dist., mkd. $\frac{1}{4}$ S15 BT.
	A fir, 41 ins. diam., bears S. $46\frac{1}{2}^{\circ}$ E., 117 lks. dist., mkd. $\frac{1}{4}$ S22 BT.
	S $89^{\circ} 20'$ W., beginning new measurement.
	Descend 12 ft. along N. slope.
0.75	Draw, drains N. 75° E.; asc. 355 ft. over E. slope.