

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 8 W.

CHAINS					
10.40	Spur, slopes S. 30° E.; desc. 430 ft. over broken SW. slope.				
30.75	Creek, 10 lks. wide, course S. 60° E.; asc. 210 ft. over NE. slope.				
37.50	Spur, slopes N. 20° E.; desc. 15 ft. over NW. slope.				
38.56	The cor. of secs. 15, 16, 21, and 22, determined at record bearing and distance from the remaining original bearing trees:				
	A cedar, 16 ins. diam., bears N. 45° E., 29 lks. dist., with old axe marks visible on bark.				
	A fir, 26 ins. diam., bears S. 85° E., 36 lks. dist., with scribe marks T31S R W B visible on bark.				
	A fir, 36 ins. diam., bears S. 85° W., 35 lks. dist., with scribe marks 8 W BT visible on bark.				
	At the corner point				
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.				
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>T 31 S R 8 W</td></tr> <tr><td>S 16 S 15</td></tr> <tr><td>S 21 S 22</td></tr> <tr><td>1961</td></tr> </table>	T 31 S R 8 W	S 16 S 15	S 21 S 22	1961
T 31 S R 8 W					
S 16 S 15					
S 21 S 22					
1961					
	from which new bearing trees				
	A fir, 25 ins. diam., bears N. 56° E., 66 lks. dist., mkd. T31S R8W S15 BT.				
	A fir, 30 ins. diam., bears N. 58° W., 110 lks. dist., mkd. T31S R8W S16 BT.				
	<p>Land, mountainous. Soil, rocky clay, loam. Timber, fir, hemlock, scattered cedar, pine, maple, and madrone; undergrowth, vine maple, huckleberry, Oregon grape, dogwood, salal, rhododendron; manzanita, poison oak, ferns and vines.</p>				
	N. 0° 45' W., bet. secs. 15 and 16.				
	Descend 5 ft. over NW. slope, through medium timber and moderate undergrowth.				
0.50	Creek, 1 lk. wide, course NE.; desc. 135 ft. over NE. slope.				
6.95	Creek, 4 lks. wide, course S. 35° E.; asc. 750 ft. over SW., changing to S. slope.				
25.00	Ridge, bears S. 60° E. and N. 60° W.; desc. 240 ft. over NE. slope.				
40.22	Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.				
	Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.				