

County Surveyor's Record, Douglas County, Oregon

21

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 8 W.

CHAINS

A fir, 37 ins. diam., bears N. $61\frac{1}{2}^{\circ}$ W., 40 lks. dist., mkd. $\frac{1}{4}$ S BT on old bark blaze. Remarked $\frac{1}{4}$ S9 BT. (Record bearing, N. 36° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ S\ 9\ | \ S\ 10 \\ T\ 31\ S\ | \ R\ 8\ W \\ 1961 \end{array}$$

from which a new bearing tree

A fir, 45 ins. diam., bears S. 56° E., 72 lks. dist., mkd. $\frac{1}{4}$ S10 BT.

N. 2° 25' W., bet. secs. 9 and 10, beginning new measurement.

Descend 25 ft. over N. slope.

- 0.75 Creek, 2 lks, wide, course E.; desc. 545 ft. over N. slope, chaning to NE. slope.
- 34.30 Creek, 3lks. wide, course E.; asc. 40 ft. over N. slope.
- 36.45 Spur, slopes N. 80° E.; desc. 46 ft. over NW. slope.
- 38.70 The cor. of secs. 3, 4, 9, and 10, determined at record distance from the remaining original bearing trees:
- A fir, 28 ins. diam., bears S. 75° E., 8 lks. dist., mkd. T R8W S10 BT on bark blaze.
- A fir, 14 ins. diam., bears S. 68° W., 27 lks. dist., mkd. with rotted face. (Record bearing, S. 52° W.)
- A fir, 16 ins. diam., bears N. 66° W., 14 lks. dist., mkd. with healed blaze. (Record bearing, N. 25° W.)
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- $$\begin{array}{r} T\ 31\ S\ | \ R\ 8\ W \\ S\ 4\ | \ S\ 8 \\ \hline S\ 9\ | \ S\ 10 \\ 1961 \end{array}$$
- from which new bearing trees
- A fir, 6 ins. diam., bears N. 65° E., 41 lks. dist., mkd. T31S R8W S3 BT.
- A fir, 17 ins. diam., bears S. $56\frac{1}{2}^{\circ}$ W., 44 lks. dist., mkd. T31S R8W S9 BT.
- A hemlock, 6 ins. diam., bears N. $27\frac{1}{2}^{\circ}$ W., 65 lks. dist., mkd. T31S R8W S4 BT.
- Land, mountainous.
Soil, rocky clay.
Timber, fir, white fir, hemlock, chinquapin, yew, pine,