

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 8 W.

CHAINS

lks. dist., mkd. T31S R8W S4 BT.

A fir, 15 ins. diam., bears S. $46\frac{1}{2}^{\circ}$ E., 53 lks. dist., mkd. T31S R8W S9 BT.

A fir, 25 ins. diam., bears S. $49\frac{1}{2}^{\circ}$ W., 46 lks. dist., mkd. T31S R8W S8 BT.

A fir, 20 ins. diam., bears N. $4\frac{1}{2}^{\circ}$ W., 29 lks. dist., mkd. T31S R8W S5 BT.

Land, mountainous.

Soil, rocky clay, loam.

Timber, fir, white fir, hemlock, chinquapin, yew, and pine; undergrowth, young timber, salal, Oregon grape, rhododendron, ferns and vines.

From the cor. of secs. 3, 4, 9, and 10.

S. 88° 13' W., bet. secs. 4 and 9.

Ascend 105 ft. over N. slope, along S. edge of logged area, through heavy timber and moderate undergrowth.

12.70 Ravine, drains N. 30° E.; asc. 275 ft. over NE. slope, changing to broken N.

34.30 Top of ascent, slopes N.; desc. 40 ft. over NW. slope.

37.80 Draw, drains N.; asc. 15 ft. over NE. slope.

38.90 The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented with a wooden post, 4 ins. square, 3 ft. above ground, firmly set, at record bearing and distance from the remains of the original bearing trees:

A rotted and broken off chinquapin stump, bears N. 72° W., 39 lks. dist.

A stump hole, with roots and bark of a chinquapin, bears S. 22° W., 19 lks. dist.

and bearing trees marked by Richard C. Grant, Registered Engineer, in 1953:

A fir, 18 ins. diam., bears N. 18° E. 40 lks. dist., with illegible scribe marks visible on partially healed blaze.

A fir, 6 ins. diam., bears S. 56° W., 23 lks. dist., with scribe marks $\frac{1}{4}$ S9 T31S R8W visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.

$\frac{1}{4}$ S 4
S 9

T 31 S R 8 W

1961

from which new bearing trees

A fir, 38 ins. diam., bears N. $49\frac{1}{2}^{\circ}$ E., 47 lks. dist., mkd. $\frac{1}{4}$ S4 BT.