

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 8 W.

CHAINS

in the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S \ 5}{S \ 8}$$

T 31 S R 8 W
1961

from which new bearing trees

A hemlock, 8 ins. diam., bears N. $3\frac{1}{2}^{\circ}$ W., 48 lks. dist., mkd. $\frac{1}{4}$ S5 BT.

A hemlock, 10 ins. diam., bears S. 18° W., 17 lks. dist., mkd. $\frac{1}{4}$ S8BT.

Land, mountainous.

Soil, rocky clay, loam.

Timber, fir, hemlock, scattered cedar, pine, madrone, maple, and chinquapin; undergrowth, live oak, huckleberry, manzanita, salal, Oregon grape, and vine maple.

The following is the description of the remonumentation of certain original cornerpoints in township 31 south, range 8 west, of the Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points With New Accessories When Needed."

The remonumentation of original corner points was made at the request of the Roseburg District Manager for administrative purposes of the Bureau of Land Management.

(Remonumenting the Corners Established by W.H. Byars in 1882 and 1883)

The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the N. bdy. of T. 31 S., R. 8 W., determined at record distance from the original bearing trees:

A fir, 34 ins. diam., bears N. 81° W., 21 lks. Dist., mkd. $\frac{1}{4}$ on a bark blaze. (Record bearing, N. 75° W.)

A hemlock, 12 ins. diam., bears S. 19° W., 29 lks. dist., with visible scribe marks on opened blaze. (Record bearing, S. 11° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

$$T \ 30 \ S \ R \ 8 \ W.$$

$$\frac{1}{4} \frac{S \ 35}{S \ 2}$$

T 31 S
1962

from which new bearing trees

A fir, 34 ins. diam., bears N. $70\frac{1}{2}^{\circ}$ E., 50 lks. dist., mkd. $\frac{1}{4}$ S35 BT.