

County Surveyor's Record, Douglas County, Oregon

31

Remonumentation, Original Corner Points, T. 31 S., R. 8 W.

CHAINS

A fir, 40 ins. diam., bears S. 67° E., 126 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

The cor. of secs. 27, 28, 33, and 34, determined at record bearing from the remaining original bearing trees:

A madrone, 8 ins. diam., bears N. 48° E. 69 lks. dist., with healed blaze. (Record distance, 68 lks.)

A sugar pine, 50 ins. diam., bears S. 21° W., 120 lks. dist., with healed blaze.

A chinquapin, 8 ins. diam., bears N. 65° W., 98 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 8 W			
S 28		S 27	
S 33		S 34	
1960			

from which new bearing trees

A sugar pine, 10 ins. diam., bears N. 41° E., 16 lks. dist., mkd. T31S R8W S27 BT.

A sugar pine, 13 ins. diam., bears S. 76° E., 41 lks. dist., mkd. T31S R8W S34 BT.

A fir, 7 ins. diam., bears N. $78\frac{1}{2}^{\circ}$ W., 32 lks. dist., mkd. T31S R8W S28 BT.

The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, determined at record bearing and distance from the original bearing trees:

A fir snag, 40 ins. diam., bears East, 62 lks. dist., to face, with no marks visible.

A fir, 45 ins. diam., bears West, 51 lks. dist., to face, with visible scribe marks on double bark blaze. Remarkd $\frac{1}{4}$ S17 BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$			
S 17		S 16	
T 31 S		R 8 W	
1962			

from which a new bearing tree

A fir, 10 ins. diam., bears S. $37\frac{1}{2}^{\circ}$ E., 46 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

The cor. of secs. 19, 20, 29, and 30, determined at record bearing and distance from the remaining original bearing trees: