

Remonumentation, Original Corner Points, T. 31 S., R. 8 W.

CHAINS

A fir, 26 ins. diam., bears S. 16° E., 48 lks. dist., with illegible scribe marks visible on bark blaze.

A fir, 28 ins. diam., bears S. 24° W., 21 lks. dist., with healed blaze.

A fir, 26 ins. diam., bears N. 66° W., .45 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T 31 S R 8 W
S 19 S 20
S 30 S 29
1960

from which a new bearing tree

A fir, 14 ins. diam., bears N. 51° E., 112 lks. dist., mkd. T31S R8W S20 BT.

The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, determined at record bearing and distance from the original bearing trees:

A fir, 36 ins. diam., bears S. 55° E., 30 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on bark blaze.

A fir, 22 ins. diam., bears N. 68° W., 56 lks. dist., with scribe marks $\frac{1}{4}$ S visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

*Fnd. O.K. by S. P. NESS #811
DEC. 1981 M 89-65*

T 31 S R 8 W
$\frac{1}{4}$
S 19 S 20
1960

The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, determined at record bearing and distance from the original NW bearing tree:

A fir, 40 ins. diam., bears N. 26° W., 5 lks. dist., mkd. $\frac{1}{4}$ S BT. Remarkd $\frac{1}{4}$ S7 BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 7
S 18
T 31 S R 8 W
1962

from which a new bearing tree

A fir, 32 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ E., 23 lks. dist., mkd. $\frac{1}{4}$ S18 BT.