

County Surveyor's Record, Douglas County, Oregon

-1-

T. 25 S., R. 2 W.

CHAINS

The following field notes describe the remonumentation of certain original corner points in township 25 south, range 2 west, of the Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories. Followed by Remonumentation of corner points, with new Accessories when needed."

The remonumentation of original corner points was made at the request of the Roseburg District Manager for administrative purposes of the Bureau of Land Management.

(Remonumenting the corners established by Hezekiah H. Johnson in 1900)

The cor. of secs. 25, 26, 35, and 36, monumented with a basalt stone, 18 x 10 x 8 ins., firmly set 11 ins. in the ground, marked with 1 notch on the S. and 1 notch on the E. edge, from which the original bearing trees:

A fir, 47 ins. diam., bears N. 23° E., 59 lks. dist., with a healed blaze. (Record bearing and distance, N. 17° E., 57 lks.)

A fir, 30 ins. diam., bears S. 70° E., 78 lks. dist., with a healed blaze.

A fir, 27 ins. diam., bears S. 31° W., 129½ lks. dist., with a healed blaze. (Record distance, 127 lks.)

A fir, 75 ins. diam., bears N. 40° W., 43 lks. dist., with a healed blaze. (Record distance, 40 lks.)

At the corner point.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

T 25 S R 2 W
S 26 | S 25
S 35 | S 36
1962

Deposit the original corner stone alongside the iron post.

The ¼ sec. cor. of secs. 25 and 36, monumented with a basalt stone, 16 x 12 x 7 ins., firmly set 11 ins. in the ground, marked ¼ on the N. face, from which the original bearing trees:

A fir, 26 ins. diam., bears N. 65° W., 33 lks. dist., with healed blaze.

A fir, 29 ins. diam., bears S. 59° W., 33 lks. dist., with healed blaze. (Record bearing, S. 61° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

¼ S 25
¼ S 36
T 25 S R 2 W
1962

Deposit the original corner stone alongside the iron post.