

County Surveyor's Record, Douglas County, Oregon

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 25 and 26, monumented with a basalt stone, 16 x 8 x 7 ins., firmly set 10 ins. in the ground, marked  $\frac{1}{4}$  on the W. face, from which the original bearing trees:

A fir, 40 ins. diam., bears S. 59° E., 29 lks. dist., with healed blaze. (Record distance, 23 lks.)

A hemlock, 28 ins. diam., bears S. 35° W., 39 lks. dist., with scribe marks  $\frac{1}{4}$  S26 visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

$\frac{1}{4}$   
S 26 | S 25  
T 25 S R 2 W  
1962

from which a new bearing tree

A cedar, 9 ins. diam., bears N. 33 $\frac{1}{2}$ ° W., 10 $\frac{1}{2}$  lks. dist., marked  $\frac{1}{4}$  S26 BT.

Deposit the original corner stone alongside the iron post.

The cor. of secs. 23, 24, 25, and 26, monumented with a basalt stone, 16 x 10 x 10 ins., firmly set 4 ins. in the ground, marked with 2 notches on the S. and 1 notch on the E. edge, from which the original bearing trees:

A hemlock, 13 ins. diam., bears N. 61° E., 75 lks. dist., with scribe mark 2 visible on partly healed blaze. (Record calls for a fir, bearing N. 59 $\frac{1}{2}$ ° E.)

A hemlock snag, 11 ins. diam., bears S. 25° E., 59 lks. dist. with scribe marks 25 BT visible on partly healed blaze. (Record bearing and distance, S. 28° E., 13 lks.)

A hemlock, 10 ins. diam., bears S. 19° W., 14 lks. dist., with scribe marks T25S R4W on rotted face of unhealed blaze. (Record bearing and distance, S. 21° W., 57 lks.)

A hemlock, 28 ins. diam., bears N. 28° W., 16 lks. dist., with a healed blaze.

At the corner point.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

T 25 S R 2 W  
S 23 | S 24  
S 26 | S 25  
1962

from which new bearing trees

A hemlock, 40 ins. diam., bears S. 87° E., 61 lks. dist., marked T25S R2W S25 BT.

A cedar, 24 ins. diam., bears S. 6 $\frac{1}{4}$ ° W., 42 lks. dist., marked T25S R4W S26 BT.

Deposit the original corner stone alongside the iron post.

Range  
# corrected  
per  
research  
10/28/2004  
JC-DCSO