

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 24 and 25, monumented with a basalt stone, 18 x 12 x 9 ins., firmly set 12 ins. in the ground, marked $\frac{1}{4}$ on the N. face, from which the original bearing trees:

A cedar, 22 ins. diam., bears N. 36° E., $11\frac{1}{2}$ lks. dist., with no marks remaining on unhealed and weathered blaze. (Record bearing and distance, N. 44° E., 10 lks.)

A hemlock snag, 20 ins. diam., bears S. 56° W., 5 lks. dist., with scribe marks 1 2 visible on partly healed blaze. (Record bearing and distance, S. 50° W., 4 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground with brass cap marked

$$\begin{array}{c} \frac{1}{4} \text{ S } 24 \\ \text{S } 25 \\ \text{T } 25 \text{ S } \text{ R } 2 \text{ W} \\ 1962 \end{array}$$

from which a new bearing tree

A cedar, 13 ins. diam., bears N. $59\frac{1}{2}^\circ$ W., 181 lks. dist., marked $\frac{1}{4}$ S24 BT.

No suitable bearing tree available in sec. 25.

Deposit the original corner stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, monumented with a basalt stone, 14 x 9 x 9 ins., firmly set 10 ins. in the ground, marked $\frac{1}{4}$ on the W. face, and perpetuated and recorded by V. W. Hosford in 1957, by driving an iron pipe, 36 ins. long, $1\frac{1}{2}$ ins. diam., 12 ins. in the ground, alongside the original corner stone, from which the original bearing trees:

A fir, 66 ins. diam., bears N. 69° E., 18 lks. dist., with a healed blaze. (Record distance, 14 lks.)

A rotted fir stump, 30 ins. diam., bears N. 37° W., 26 lks. dist., with scribe marks $\frac{1}{4}$ S23 visible on opened blaze. (Record bearing and distance, N. 32° W., 24 lks.)

and a tree marked by Hosford

A broken hemlock, 8 ins. diam., bears N. 80° W., 100 lks. dist., with scribe marks $\frac{1}{4}$ S23 253 BT visible on unhealed blaze on down trunk.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 23 \text{ | } \text{S } 24 \\ \text{T } 25 \text{ S } \text{ R } 2 \text{ W} \\ 1962 \end{array}$$

from which a new bearing tree

A hemlock, 4 ins. diam., bears N. 76° W., 61 lks. dist., marked $\frac{1}{4}$ S23 BT.

Deposit the original corner stone and reset the iron pipe alongside the iron post.