

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

The $\frac{1}{4}$ Sec. Cor. of secs. 13 and 14, perpetuated and recorded by V. W. Hosford in 1957, monumented with an iron pipe, 36 ins. long, $1\frac{1}{2}$ ins. diam., firmly set 22 ins. in the ground, from which the original bearing trees:

A fir, 44 ins. diam., bears N. 54° E., 14 lks. dist., with healed blaze. (Record distance, 12 lks.)

A hemlock snag, 16 ins. diam., bears N. 58° W., 19 lks. dist., with fragmentary scribe marks visible on unhealed blaze. (Record distance, 18 lks.)

and a tree marked by Hosford

A hemlock, 22 ins. diam., bears N. $30\frac{1}{2}^{\circ}$ W., 40 lks. dist., with scribe marks $\frac{1}{4}$ S14 253 BT visible on unhealed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked.

$\frac{1}{4}$
 S 14 | S 13
 T 25 S | R 2 W
 1962

from which a new bearing tree

A hemlock, 11 ins. diam., bears N. $66\frac{1}{4}^{\circ}$ W., 36 lks. dist., marked $\frac{1}{4}$ S14 BT.

Reset iron pipe alongside the iron post.

The cor. of secs. 11, 12, 13, and 14, monumented with a basalt stone, 16 x 10 x 6 ins., firmly set 11 ins. in the ground, marked with 4 notches on the S., and 1 notch on the E. edge, from which the original bearing trees:

A fir, 46 ins. diam., bears N. $18\frac{1}{2}^{\circ}$ E., 43 lks. dist., with healed blaze. (Record bearing and distance, N. 25° E., 41 lks.)

A fir, 58 ins. diam., bears S. 30° E., 18 lks. dist., with healed blaze. (Record bearing and distance, S. 23° E., 15 lks.)

A fir snag, 15 ins. diam., bears S. 57° W., 31 lks. dist., with scribe marks 25 S R2W S14 visible on unhealed blaze. (Record bearing, S. 55° W.)

A hemlock, 20 ins. diam., bears N. 72° W., 26 lks. dist., with scribe marks T25S R2W S11 visible on opened blaze. (Record bearing, N. 76° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 25 S R 2 W
 S 11 | S 12
 S 14 | S 13
 1962

from which a new bearing tree