

County Surveyor's Record, Douglas County, Oregon

-6-

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

A hemlock, 9 ins. diam., bears S. 6° W., 72 lks. dist., marked T25S R2W S14 BT.

Deposit the original corner stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, determined at record bearing and distance, from the faces of the original bearing trees:

A fir, 19 ins. diam., bears N. 34° E., 20 lks. dist., with healed blaze. (Record distance, 19 lks.)

A sawed fir stump, 39 ins. diam., bears S. 54° W., 19 lks. dist., with healed blaze. (Record distance, 17 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap marked.

$$\begin{array}{r} \frac{1}{4} \text{ S } 12 \\ \frac{1}{4} \text{ S } 13 \\ \text{T } 25 \text{ S } \text{ R } 2 \text{ W} \\ 1962 \end{array}$$

from which a new bearing tree

A hemlock, 13 ins. diam., bears South, 43 lks. dist., marked $\frac{1}{4}$ S13 BT.

The cor. os secs. 26, 27, 34 and 35, monumented with a basalt stone, 16 x 12 x 8 ins., firmly set 7 ins. in the ground, marked with 1 notch on the S. and 2 notches on the E. edge, and perpetuated and recorded by G. Robert Lecklider in 1960, with a steel tube, 36 ins. long, $\frac{3}{4}$ ins. diam., topped with an unmarked aluminum cap, firmly set 24 ins. in the ground, alongside the corner stone, from which the original bearing trees:

A down hemlock, 11 ins. diam., bears N. 13° E., 14 lks. dist., with a healed blaze. (Record bearing, N. 15° E.)

A hemlock, 18 ins. diam., bears East, 26 lks. dist., with a healed blaze. (Record bearing, S. 85° E.)

A hemlock, 10 ins. diam., bears S. 14 $\frac{1}{2}$ ° W., 43 lks. dist., with a healed blaze. (Record bearing and distance, N. 59° W., 35 lks.)

and trees marked by Lecklider

A hemlock, 15 ins. diam., bears N. 82° E., 51 lks. dist., with scribe marks S26 RE4079 BT visible on unhealed double blaze.

A down hemlock, 16 ins. diam., bears S. 46° E., 40 lks. dist., with scribe marks S35 RE4079 BT visible on an unhealed double blaze.

A down hemlock, 10 ins. diam., bears S. 64° W., 44 lks. dist., with scribe marks S34 RE4079 BT visible on an unhealed double blaze.

A hemlock, 9 ins. diam., bears N. 57° W., 47 lks. dist., with scribe marks S27 RE4079 BT visible on an unhealed double blaze.