

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground with brass cap marked

T 25 S R 2 W
S 27 S 26
S 34 S 35
1962

Deposit the original corner stone and reset the steel tube alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented with a basalt stone, 14 x 10 x 6 ins., firmly set 10 ins. in the ground, marked $\frac{1}{4}$ on the W. face, from which the original bearing trees:

A yew, 11 ins. diam., bears S. 81° E., 32 lks. dist., with fragmentary scribe marks visible on partly healed blaze.

A yew, 9 ins. diam., bears S. 85° W., 34 lks. dist., with no marks remaining on rotted blaze. (Record bearing, S. 80° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap marked

$\frac{1}{4}$
S 27 S 26
T 25 S R 2 W
1962

from which a new bearing tree

A fir, 42 ins. diam., bears S. $19\frac{1}{2}^{\circ}$ W., 41 lks. dist., marked $\frac{1}{4}$ S27 BT.

Deposit the original corner stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, monumented with a basalt stone, 16 x 10 x 6 ins., firmly set 11 ins. in the ground, marked $\frac{1}{4}$ on the N. face, from which the original bearing trees:

A hemlock, 26 ins. diam., bears N. $56\frac{1}{2}^{\circ}$ E., 56 lks. dist., with a healed blaze. (Record bearing and distance, N. 53° E., 53 lks. dist.)

A hemlock, 14 ins. diam., bears S. 25° E., 31 lks. dist., with scribe mark 4 visible on partly opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 23
$\frac{1}{4}$ S 26
T 25 S R 2 W
1962

from which a new bearing tree