

County Surveyor's Record, ₋₈₋ Douglas County, Oregon

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

A hemlock, 26 ins. diam., bears S. 3° E., 70 lks. dist.,
marked $\frac{1}{4}$ S26 BT.

Deposit the original corner stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented with a basalt stone,
14 x 10 x 6 ins., firmly set 10 ins. in the ground, marked $\frac{1}{4}$ on
the N. face, from which the original bearing trees:

A hemlock, 14 ins. diam., bears N. 42° W., 18 lks. dist.,
with scribe mark S visible on partly opened blaze.

A hemlock, 20 ins. diam., bears S. 3° W., 32 lks. dist.,
with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground,
with brass cap marked

$$\frac{1}{4} \frac{S \ 14}{S \ 23}$$

T 25 S R 2 W

1962

from which a new bearing tree

A hemlock, 15 ins. diam., bears N. 46° E., 32 lks. dist.,
marked $\frac{1}{4}$ S14 BT.

Deposit the original corner stone alongside and break a
clear glass bottle at base of the iron post.

The $\frac{1}{4}$ Sec. cor. of secs. 11 and 14, monumented with a basalt stone,
20 x 8 x 5 ins., firmly set 15 ins. in the ground, marked $\frac{1}{4}$ on the
N. face, from which the only remaining original bearing tree:

A cedar, 21 ins. diam., bears N. 4° W., 11 lks. dist.,
with scribe mark 4 visible on an opened blaze.
(Record bearing & distance, N. 25° E., 10 lks.)

and a bearing tree of which I have no record

A hemlock, 10 ins. diam., bears S. 62° W., 26 lks. dist.,
with scribe marks T25S R2W $\frac{1}{4}$ S14 CS BT on unhealed
double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground,
with brass cap marked

$$\frac{1}{4} \frac{S \ 11}{S \ 14}$$

T 25 S R 2 W

1962

from which a new bearing tree

A cedar, 5 ins. diam., bears N. 8° E., 34 lks. dist.,
marked $\frac{1}{4}$ S11 BT.

Deposit the original corner stone alongside the iron post.