

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 10 and 11, determined at record bearing and distance from the original bearing trees:

A cedar, 18 ins. diam., bears S.  $64^\circ$  E., 54 lks. dist., with no marks remaining on a burned-out blaze.

A fir, 55 ins. diam., bears N.  $52^\circ$  W., 40 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked

*FD OK 2/92  
G. LANG M 114-57  
FD OK S. JESS 1095  
M 123-3 A & B*

$\frac{1}{4}$   
S 10 | S 11  
T 25 S R 2 W  
1962

from which a new bearing tree

A hemlock, 9 ins. diam., bears S.  $24\frac{1}{2}^\circ$  E., 35 lks. dist., marked  $\frac{1}{4}$  S11 BT.

The  $\frac{1}{4}$  sec. cor. of secs. 33 and 34, monumented with a basalt stone, 16 x 12 x 6 ins., firmly set 11 ins. in the ground, marked  $\frac{1}{4}$  on the W. face, from which the original bearing trees:

A fir, 44 ins. diam., bears N.  $64^\circ$  E.,  $75\frac{1}{2}$  lks. dist., with a healed blaze. (Record bearing and distance, N.  $62\frac{1}{2}^\circ$  E., 80 lks.)

A fir, 16 ins. diam., bears S.  $53^\circ$  W., 50 lks. dist., with a healed blaze. (Record bearing S.  $52^\circ$  W.)

and bearing trees marked by G. Robert Lecklider in 1960

A fir, 18 ins. diam., bears S.  $38\frac{1}{2}^\circ$  E.,  $20\frac{1}{2}$  lks. dist., with scribe marks  $\frac{1}{4}$  S34 RE4,079 BT visible on unhealed double blaze.

A fir, 12 ins. diam., bears N.  $23^\circ$  W., 22 lks. dist., with scribe marks  $\frac{1}{4}$  S33 RE4,079 BT visible on unhealed double blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone,  $2\frac{1}{2}$  ft. base, to top, with brass cap marked

$\frac{1}{4}$   
S 33 | S 34  
T 25 S R 2 W  
1962

Deposit the original corner stone alongside the iron post.

The cor. of secs. 27, 28, 33 and 34, monumented with the original basalt stone, 18 x 9 x 9 ins., firmly set 12 ins. in the ground, marked with 1 notch on the S. and 3 notches on the E. edge, and witnessed by a mound of stone, 2 ft. base, 1 ft. high, W. of corner.

from which locally established bearing trees