

County Surveyor's Record, Douglas County, Oregon

-11-

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, determined at record bearing & distance from the only remaining original bearing tree:

A fir, 45 ins. diam., bears S. 42° E., 27 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 28 \text{ | } \text{S } 27 \\ \text{T } 25 \text{ S | R } 2 \text{ W} \\ 1962 \end{array}$$

From which a new bearing tree

A hemlock, 18 ins. diam., bears N. 10° W., 24 lks. dist., marked $\frac{1}{4}$ S28 BT.

The cor. of secs. 21, 22, 27 and 28, monumented with a basalt stone, 16 x 8 x 6 ins., firmly set 10 ins. in the ground, marked with 2 notches on the S. and 3 notches on the E. edge, from which the original bearing trees:

A hemlock, 17 ins. diam., bears N. $12\frac{1}{2}^\circ$ E., 31 lks. dist., with a healed blaze.

A chinquapin snag, 18 ins. diam., bears S. 38° W., 14 lks. dist., with a healed blaze. (Record bearing, S. 42° W.)

A fir, 37 ins. diam., bears N. 75° W., 53 lks. dist., with a healed blaze. (Record distance, 51 lks.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{T } 25 \text{ S } \text{R } 2 \text{ W} \\ \text{S } 21 \text{ | } \text{S } 22 \\ \text{S } 28 \text{ | } \text{S } 27 \\ 1962 \end{array}$$

from which new bearing trees

A chinquapin, 8 ins. diam., bears S. 62° E., 46 lks. dist., marked T25S R2W S27 BT.

A chinquapin, 4 ins. diam., bears S. $54\frac{1}{2}^\circ$ W., $37\frac{1}{2}$ lks. dist., marked T25S R2W S28 BT.

Deposit the original corner stone alongside and break a clear glass bottle at base of the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented with a basalt stone, 18 x 8 x 5 ins., firmly set 12 ins. in the ground, marked $\frac{1}{4}$ on the N. face, from which the original bearing trees:

A rotted hemlock stump, 16 ins. diam., bears N. 34° W., 26 lks. dist., with scribe marks BT visible on opened blaze.

A cedar, 19 ins. diam., bears S. $24\frac{1}{2}^\circ$ E., 22 lks. dist., with scribe marks $\frac{1}{4}$ S27 visible on partly healed blaze. (Record bearing and distance, S. 22° E., 21 lks.)