

County Surveyor's Record, Douglas County, Oregon

-14-

Remonumentation of Certain Original Corner Points, T. 25 S. R. 2 W.

CHAINS

A fir, 57 ins. diam., bears N. 37° E., 20 lks. dist., with a healed blaze. (Record bearing distance, N. 44° E., 17 lks.)

A broken fir stump, 26 ins. diam., bears S. 26° E., 71 lks. dist., with scribe marks T25S R2W S15 visible on an unhealed blaze on fallen trunk. (Record bearing & distance, S. 29° E., 75 lks.)

A down fir, 14 ins. diam., bears S. 33° W., 34 lks. dist., with no marks remaining.

A fir, 15 ins. diam., bears N. 40° W., 40 lks. dist., with a healed blaze. (Record bearing, N. 35° W.)

and bearing trees marked by Ben Irving, County Surveyor, 1958

A fir, 50 ins. diam., bears S. 32½° E., 70 lks. dist., marked T25S R2W S15 CS BT, on bark.

A sawed fir stump, 36 ins. diam., bears S. 5° W., 61 lks. dist., marked T25S R2W S16 BT, on bark.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap marked

*Book 2/92
GLAUG M 114-57*

T 25 S R 2 W			
S 9	S 10		
S 16	S 15		
1962			

from which a new bearing tree

A fir, 16 ins. diam., bears S. 36° W., 55 lks. dist., marked T25S R2W S16 BT.

Deposit the original corner stone alongside the iron post.

The corner falls under a fallen fir, 48 ins. diam.

The ¼ sec. cor. of secs. 10 and 15, monumented with a basalt stone, 14 x 10 x 6 ins., firmly set 6 ins. in the ground, marked ¼ on the N. face, from which the original bearing trees:

A chinquapin snag, 8 ins. diam., bears N. 17° W., 32 lks. dist., with no marks remaining on decayed blaze.

A chinquapin snag, 7 ins. diam., bears S. 10° E., 38 lks. dist., with no marks remaining on decayed blaze. (Record bearing, S. 12° E.)

and bearing trees marked by Ben Irving, County Surveyor in 1958

A fir, 85 ins. diam., bears N. 68° W., 35 lks. dist., marked T25S R2W S10 CS BT, on bark.

A sawed fir stump, 11 ins. diam., bears S. 50° E., 58 lks. dist., with a healed blaze on down trunk.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked