

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

FD. or 242
G. LANE M 114-57

$\frac{1}{4}$ S 10
 $\frac{1}{4}$ S 15
T 25 S R 2 W
1962

from which new bearing trees

A chinquapin, 12 ins. diam., bears N. $30\frac{1}{2}^{\circ}$ E., 63 lks. dist.,
marked $\frac{1}{4}$ S10 BT.

A fir, 8 ins. diam., bears S. $3\frac{1}{2}^{\circ}$ E., 59 lks. dist.,
marked $\frac{1}{4}$ S15 BT.

Deposit the original corner stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with a basalt stone,
16 x 10 x 8 ins., firmly set 11 ins. in the ground, marked $\frac{1}{4}$ on
the W. face, from which the original bearing trees:

A down yew, 11 ins. diam., bears S. 56° E., 45 lks. dist.,
with no marks remaining.

A down yew, 8 ins. diam., bears N. 75° W., 20 lks. dist.,
with no marks remaining.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground,
with brass cap marked

$\frac{1}{4}$
S 9 | S 10
T 25 S R 2 W
1962

from which new bearing trees

A cedar, 32 ins. diam., bears S. $45\frac{1}{2}^{\circ}$ E., 91 lks. dist.,
marked $\frac{1}{4}$ S10 BT.

A hemlock, 27 ins. diam., bears N. 26° W., 100 lks. dist.,
marked $\frac{1}{4}$ S9 BT.

and an original line tree

A fir, 92 ins. diam., bears North, 203 lks. dist.,
marked with 2 notches on the N. and 2 notches on the
S. side.

Deposit the original corner stone alongside the iron post.

The cor. of secs. 28, 29, 32 and 33, monumented with a shattered
basalt stone, 3 x 2 x $1\frac{1}{2}$ ft., above ground, marked with an X on
top, and 1 notch on the S. and 3 notches on the E. edge, from which
the original bearing trees:

A down and rotted pine, 12 ins. diam., bears N. 31° E.,
28 lks. dist., with no marks remaining.

A maple, 9 ins. diam., bears S. 11° E., 27 lks. dist.,
with a healed blaze. (Record bearing, S. 15° E.)

A fir, 65 ins. diam., bears S. 29° W., 32 lks. dist.,
with no marks visible on partly opened blaze. (Record
bearing and distance, S. 25° W., 30 lks.)