

County Surveyor's Record, Douglas County, Oregon

-16-

Remonumentation of Certain Original Corner Points T. 25 S., R. 2 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

T 25 S R 2 W
S 29 S 28
S 32 S 33
1962

from which a new bearing tree and a bearing object

The W. face of a rock outcrop, bears N. 80° E., 3½ lks. dist., marked X BO.

A hemlock, 20 ins. diam., bears N. 21° W., 38½ lks. dist., marked T25S R2W S29 BT.

Deposit the original corner stone around the iron post, in the form on a mound, 3 ft. base, to top.

The ¼ sec. cor. of secs. 28 and 33, monumented with a basalt stone, 16 x 12 x 4 ins., firmly set 11 ins. in the ground, marked ¼ on the N. face, from which the only remaining original bearing tree:

A cedar, 60 ins. diam., bears N. 35° W., 80 lks. dist., with no marks remaining on burned-out blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

¼ S 28
¼ S 33
T 25 S R 2 W
1962

from which new bearing trees

A fir, 24 ins. diam., bears N. 40½° W., 50 lks. dist., marked ¼ S28 BT.

A fir, 28 ins. diam., bears S. 25° E., 7½ lks. dist., marked ¼ S33 BT.

Deposit the original corner stone alongside the iron post.

The ¼ sec. cor. of secs. 28 and 29, monumented with a basalt stone, 22 x 10 x 8 ins., loosely set 6 ins. in the ground, marked ¼ on the W. face, from which the original bearing trees:

A hemlock, 26 ins. diam., bears N. 39° E., 31 lks. dist., with a healed blaze. (Record bearing, N. 41° E.)

A rotted fir snag, 18 ins. diam., bears S. 84° W., 59 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record bearing, S. 81° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap marked