

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

$$\begin{array}{c} \frac{1}{4} \\ S\ 29\ | S\ 28 \\ T\ 25\ S\ R\ 2\ W \\ 1962 \end{array}$$

from which a new bearing tree and a bearing object

The W. face of a rock outcrop, under overhang, bears
S. $70\frac{1}{4}^{\circ}$ E., $36\frac{1}{2}$ lks. dist., marked X BC.

A cedar, 10 ins. diam., bears N. $68\frac{1}{2}^{\circ}$ W., $42\frac{1}{2}$ lks. dist.,
marked $\frac{1}{4}$ S29 BT.

Deposit the original corner stone alongside the iron post.

The cor. of secs. 20, 21, 28 and 29, perpetuated and recorded by
V. W. Hosford in 1957, monumented with an iron pipe, 36 ins. long,
 $1\frac{1}{2}$ ins. diam., firmly set 24 ins. in the ground, from which the
original bearing trees:

A white fir, 20 ins. diam., N. 35° E., 56 lks. dist.,
with a healed blaze.

A cedar, 22 ins. diam., bears S. 45° E., 10 lks. dist.,
with a healed blaze.

A sawed fir, stump, 52 ins. diam., bears S. 13° W., 29 lks.
dist., with scribe marks S S2 visible on opened and
rotted blaze. (Record distance, 25 lks.)

A sawed white fir stump, 27 ins. diam., bears N. 57° W.,
71 lks. dist., with a healed blaze.

and bearing trees marked by Hosford

A hemlock, 6 ins. diam., bears S. $13\frac{1}{2}^{\circ}$ W., 91 lks. dist.,
with fragmentary scribe marks visible on nearly healed
blaze.

A broken top cedar, 24 ins. diam., bears West, 52 lks.
dist., with scribe marks S20 253 BT visible on unhealed
blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground,
and in a mound of stone, 2 ft. base, to top, with brass cap marked

$$\begin{array}{c} T\ 25\ S\ R\ 2\ W \\ S\ 20\ | S\ 21 \\ S\ 29\ | S\ 28 \\ 1962 \end{array}$$

No suitable bearing tree available in sec. 20.

Reset the iron pipe alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, monumented with a basalt stone,
18 x 10 x 8 ins., firmly set 11 ins. in the ground, marked $\frac{1}{4}$ on the
N. face, perpetuated and recorded by V. W. Hosford in 1957, with an
iron pipe, 36 ins. long, $1\frac{1}{2}$ ins. diam., 12 ins. in the ground
alongside the original corner stone, from which the only remaining
original bearing tree:

A rotted fir stump, 34 ins. diam., bears S. $25\frac{1}{2}^{\circ}$ E.,
47 lks. dist., with no marks remaining. (Record
bearing and distance, S. 21° E., 45 lks.)