

County Surveyor's Record, Douglas County, Oregon

-20-

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

A sawed fir stump, 28 ins. diam., bears S. 45° E., 25 lks. dist., with a healed blaze. (Record bearing, S. 40° E.)

A fir snag, 30 ins. diam., bears S. $44\frac{1}{2}^{\circ}$ W., 49 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \uparrow \\ \text{S } 17 \mid \text{S } 16 \\ \text{T } 25 \text{ S } \text{ R } 2 \text{ W} \\ 1962 \end{array}$$

from which new bearing trees

A fir, 50 ins. diam., bears N. 30° E., 82 lks. dist., marked $\frac{1}{4}$ S16 BT.

A maple, 9 ins. diam., bears S. 30° W., 79 lks. dist., marked $\frac{1}{4}$ S17 BT.

The cor. of secs. 8, 9, 16 and 17, determined at record bearing & distance from the original bearing trees:

A fir, 25 ins. diam., bears N. 37° E., 53 lks. dist., with a healed blaze.

A hemlock, 9 ins. diam., bears S. 21° E., 9 lks. dist., with scribe marks 25S R2W S1 visible on opened blaze.

A fir, 9 ins. diam., bears S. 25° W., 76 lks. dist., with fragmentary scribe marks visible on opened blaze.

A dogwood, 6 ins. diam., bears N. 45° W., 21 lks. dist., with fragmentary scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, & in a mound of stone, 3 ft. base, to top, with brass cap marked

$$\begin{array}{c} \text{T } 25 \text{ S } \text{ R } 2 \text{ W} \\ \text{S } 8 \mid \text{S } 9 \\ \text{S } 17 \mid \text{S } 16 \\ 1962 \end{array}$$

from which new bearing trees and a bearing object

A fir, 38 ins. diam., bears S. $14\frac{1}{2}^{\circ}$ E., 41 lks. dist., marked T25S R2W S16 BT.

The E. face of a rock outcrop, bears S. $57\frac{3}{4}^{\circ}$ W., 14 lks. dist., marked X B0.

A cedar, 25 ins. diam., bears N. 9° W., $58\frac{1}{2}$ lks. dist., marked T25S R2W S8 BT.

The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented with a basalt stone, 14 x 12 x 4 ins., firmly set 10 ins. in the ground, marked $\frac{1}{4}$ on the N. face, from which the original bearing trees:

A fir, 32 ins. diam., bears N. 27° E., 4 lks. dist., with a healed blaze.