

County Surveyor's Record, <sup>222-</sup>Douglas County, Oregon

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

$\frac{1}{4}$   
 S 31 | S 32  
 T 25 S | R 2 W  
 1962

FD BOOK  
 8/9/84  
 R. GEISLER  
 C.S. 58/146  
 (FD FIR BBE. TO BE SE)

from which a new bearing tree

A fir, 10 ins. diam., bears N.  $88\frac{1}{2}^{\circ}$  E., 85 lks. dist., marked  $\frac{1}{4}$  S32 BT.

Deposit the original corner stone alongside the iron post.

The cor. of secs. 29, 30, 31 and 32, monumented with a basalt stone, 16 x 8 x 6 ins., firmly set 11 ins. in the ground, marked with 1 notch on the S., and 5 notches on the E. edge, from which the original bearing trees:

A chinquapin, 17 ins. diam., bears N.  $36^{\circ}$  E., 36 lks. dist., with no marks remaining on decayed blaze. (Record distance, 35 lks.)

A chinquapin, 14 ins. diam., bears S.  $44\frac{1}{2}^{\circ}$  E., 33 lks. dist., with fragmentary scribe marks visible on nearly healed blaze. (Record distance, 32 lks.)

A chinquapin, 14 ins. diam., bears S.  $13^{\circ}$  W., 41 lks. dist., with a healed blaze.

A fir, 24 ins. diam., bears N.  $12\frac{1}{2}^{\circ}$  W., 51 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap marked

T 25 S R 2 W  
 S 30 | S 29  
 S 31 | S 32  
 1962

from which a new bearing tree

A fir, 20 ins. diam., bears N.  $78^{\circ}$  E., 21 lks. dist., marked T25S R2W S29 BT.

Deposit the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 29 and 32, monumented with a basalt stone, 18 x 9 x 8 ins. firmly set 12 ins. in the ground, marked  $\frac{1}{4}$  on the N. face, from which the original bearing trees:

A fir, 34 ins. diam., bears N.  $18^{\circ}$  W., 112 lks. dist., with a healed blaze. (Record bearing and distance, N.  $15^{\circ}$  W., 118 lks. dist.)

A fir, 32 ins. diam., bears S.  $43^{\circ}$  E., 12 lks. dist., with a healed blaze. (Record bearing and distance, S.  $53^{\circ}$  E., 111 lks.)

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 25 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

$\frac{1}{4}$  S 29  
 $\frac{1}{4}$  S 32  
 T 25 S R 2 W  
 1962