

## Remonumentation of Certain Original Corner Points, T. 25 S. R. 2 W.

CHAINS

Deposit the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 30 and 31, determined at record bearing & distance from the only remaining original bearing tree:

A white fir, 34 ins. diam., bears S.  $20^{\circ}$  W., 62 lks. dist., with scribe marks BT visible on partly opened blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \text{ S } 30 \\ \frac{1}{4} \text{ S } 31 \\ \text{T } 25 \text{ S } \text{ R } 2 \text{ W} \\ 1962 \end{array}$$

from which new bearing trees

A cottonwood, 16 ins. diam., bears N.  $7\frac{1}{2}^{\circ}$  W., 62 lks. dist., marked  $\frac{1}{4}$  S30 BT.

A hemlock, 19 ins. diam., bears S.  $32\frac{1}{2}^{\circ}$  W., 77 lks. dist., marked  $\frac{1}{4}$  S31 BT.

The  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, monumented with a basalt stone, 16 x 8 x 6 ins., loosely set 5 ins. in the ground, marked  $\frac{1}{4}$  on the W. face, from which the original bearing trees:

A white fir, 28 ins. diam., bears S.  $72\frac{1}{2}^{\circ}$  E., 52 lks. dist., with a healed blaze. (Record bearing and distance, S.  $69^{\circ}$  E., 48 lks.)

A fir, snag, 42 ins. diam., bears N.  $56\frac{1}{4}^{\circ}$  W., 126 $\frac{1}{2}$  lks. dist., with a healed blaze. (Record bearing and distance, N.  $55^{\circ}$  W., 128 lks.)

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 30 \text{ | } \text{S } 29 \\ \text{T } 25 \text{ S } \text{ R } 2 \text{ W} \\ 1962 \end{array}$$

from which a new bearing tree

A fir, 15 ins. diam., bears N.  $15^{\circ}$  W., 50 lks. dist., marked  $\frac{1}{4}$  S30 BT.

Deposit the original corner stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 20 and 29, monumented with a basalt stone, 18 x 8 x 5 ins., firmly set 12 ins. in the ground, marked  $\frac{1}{4}$  on the N. face, from which the original bearing trees:

A rotted fir stump, 19 ins. diam., bears N.  $27^{\circ}$  E., 67 lks. dist., with a healed blaze. (Record bearing, N.  $25^{\circ}$  E.)

A fir, 18 ins. diam., bears S.  $50^{\circ}$  E., 54 lks. dist., with a healed blaze. (Record bearing, S.  $48^{\circ}$  E.)